

## NOTES:

- 1. EARTHWORK, AGGREGATE BASE, AND HOT MIX ASPHALT (HMA) SHALL CONFORM TO SECTIONS 19,
- 26 AND 39 OF THE STATE STANDARD SPECIFICATIONS, LATEST EDITION.
  2. CALCULATE THE STRUCTURAL SECTION PER CALTRANS PROCEDURES FOR FLEXIBLE PAVEMENT USING A TRAFFIC INDEX (T.I.) OF 4.5 AND THE PROJECT'S R-VALUE OF THE SUBGRADE.
- 3. 2' CONCRETE VALLEY GUTTER PER COUNTY STD. DWG. ST-1B IS REQUIRED AT CENTER LINE IF LONGITUDINAL SLOPE IS  $\leq$  0.02.
- 4. TYPE A HMA AGGREGATE GRADATION SHALL BE  $\frac{1}{2}$ " MAXIMUM, MEDIUM.

| DRAWN BY    |          | COUNTY OF MADERA                     | DRAWING NO. |
|-------------|----------|--------------------------------------|-------------|
| DATE _      | 3/5/1980 | COMMERCIAL AND<br>RESIDENTIAL ALLEYS | ST-12       |
| REVISED BY_ | J.S.C.   |                                      |             |
| DATE _      | 3/2/2011 |                                      |             |