


CORNER RECORD

COUNTY OF Madera T. 5 S. R. 23 E. M.D.B. & M. MERIDIAN CALIFORNIA

CORNER TYPE: GOVT. CORNER MEANDER RANCHO CONTROL OTHER
CORNER IDENTIFICATION - DATE OF VISIT August 20 19 85



The west 1/4 corner of section 15 5/23.

CORNER - LEFT AS FOUND POUND AND TAGGED REESTABLISHED OBLITERATED CORNER RESULT

PHYSICAL DESCRIPTION OF CORNER FOUND; EVIDENCE AND METHOD USED TO IDENTIFY OR REESTABLISH
Found and Accepted: A 21" dia. Fir with blazes on the east and west sides and 2 original bearing trees per GLO field notes of J. M. Anderson U.S. Deputy Surveyor 1881.

PHYSICAL DESCRIPTION OF MONUMENTS RESULT OR PERPETUATED
Set 2 F.S.M.'s as Reference Monuments for the corner. (See Corner Ties)

F.S.M. - Aluminum monument, 2 1/2" O.D., 30" long with a 3 1/4" O.D. aluminum cap stamped for the corner, with LS 4689, the date and the Forest Service logo.

CALIFORNIA COORDINATE SYSTEM ORDER: FIRST SECOND THIRD
STATIONS USED: NGS (USC & GS) STATE COUNTY OTHER STATION _____ STATION _____
ZONE _____ ELEVATION _____ NORTHINGS (Y) _____ EASTINGS (X) _____

SKETCH: (Include reference tie or witness points, remarks and topo of area)

Corner Ties:

Original Bearing Trees:

1. A Fir stump, 50" dia. bears S 41° 55' E, 13.7'. (No Nail)
2. A Fir stump, 38" dia., bears S 77° 57' W, 16.9'. (No Nail)

Other Ties:

3. Found a 1 1/4" O.D.I.P., up 9", with a 2 1/2" dia. brass cap stamped as a Witness Corner and with LS 4126 (See Cap Inscription on back), bears N 0° 57' 43" W, 4.00'.
4. Reference Monument #1 - Set F.S.M., up 7", N 45° 00' 00" E, 25.00'. Built a rock mound 2' dia. x 1' high around monument. Set a metal post with Forest Service monument signs attached 4' ± NE of monument. (See Cap Inscription on back).

L-13
F.B. 35/30
Job No. 85-11
(Continued on back)

SURVEYOR'S CERTIFICATE
THIS CORNER RECORD WAS PREPARED BY ME OR UNDER MY
DIRECTION IN CONFORMANCE WITH THE LAND SURVEYORS ACT
ON November 25 19 85
SIGNED: Harold Donald Cohen
L.S. NUMBER No. 4126



COUNTY SURVEYOR'S CERTIFICATE
THE CORNER RECORD WAS RECEIVED _____ 19 ____
AND EXAMINED AND FILED _____
BY: Harold Donald Cohen
TITLE: _____

DOCUMENT No. _____
STATEMENT ON BACK OF SHEET YES NO

5. Reference Monument # 2 - Set F.S.M., up 7", N 45° 00' 00" W, 25.00'. Built a rock mound 2 1/2' dia. x 1' high around monument. Set a metal post with Forest Service monument signs attached 4' ± NW of the corner.

6. A Fir 24.8" dia, bears S 50° 05' E, 64.44'.

7. A Fir 21.6" dia., bears N 83° 16' W, 89.03'.

Cap Inscriptions:

Reference Monument # 1

S 15
R M
25.00 FT
TO COR
LS 4689
1985

Reference Monument # 2

R M
25.00 FT
TO COR
S 16
LS 4689
1985

Witness Corner

T 5 S R 23 E
WIT. COR.
16 - 15
1/4 COR
LS 4126 10 10 76

Bearings are to the center of trees at the base. Distances are horizontal to a nail and tag (stamped LS 4689) driven into the side center of the root crown, unless otherwise noted.

Posted Forest Service monument and bearing tree signs.

Stamped monuments in accordance with the BLM 1973 " Manual of Surveying Instructions".

0523 400 440

