COMMENT FOR SOVIL COMMENT MANAGER AND ADDRESS OF COMMENT OF THE STATE	COUNTY OF Madera	T. 5 S.	23 1		D.B. & M.	METIDIAN	CAUPOR
The south 1/16 corner of section 27 5/23.  (Cormen to sections 27 and 28)  CONNET LET AS FOLHO POLYCOLOGY AND TAGGED PROJECT SECTION OF COUNTY SURVIVERS COUNTY SURVIVERS OF SECTION OF COUNTY SURVIVERS OF SECTION OF COUNTY SURVIVERS OF SECTION OF SECTION OF COUNTY SURVIVERS OF SECTION O		MEANOER	ZANCHO 🗆	CONTROL		ACCIDIAN	CAUPOR
COMMENT SUSTINGS OF STATES	CORNER IDENTIFICATION D	ATE OF VISITAUG	ust 12	<u>85                                    </u>			
COMMON TO SECTIONS 27 and 28)  COMMON AND TAGGED SECTION CONTRACTOR CONTRACTO	The s	south 1/16 corne	r of section	27 5/23			
PATRICAL DESCRIPTION OF CORNER FOUND, INTERNET AND METHOD USED TO DESCRIPTION OF MEDITAL DESCRIPTION OF MONOMENTS AND METHOD USED TO DESCRIPTION OF MONOMENTS MEASURE (See sketch on back)  PATRICAL DESCRIPTION OF MONOMENTS MONOMENTS MONOMENTS MONOMENTS MO				1 3/-3.	a -		
PATRICAL DESCRIPTION OF COMMER FOUND. PURDENCE AND METHOD USED TO IDENTIFY OF RESTAUSING FOUND AND ACCEPTED: A 1" O.D.I.P., 24" long, up 7", tagged RCE 21650. Corner position established by subdivision of section procedure.  (See sketch on back)  PATRICAL DESCRIPTION OF MCHUMENTS MEMBLY OR PERPETUATED (See sketch on back)  PATRICAL DESCRIPTION OF MCHUMENTS MEMBLY OR PERPETUATED (See sketch on back)  PATRICAL DESCRIPTION OF MCHUMENTS MEMBLY OR PERPETUATED (See sketch on back)  PATRICAL DESCRIPTION OF MCHUMENTS MEMBLY OR PERPETUATED (See sketch on back)  PATRICAL DESCRIPTION OF MCHUMENTS MEMBLY OR PERPETUATED (See sketch on back)  PATRICAL DESCRIPTION OF MCHUMENTS MEMBLY OR PERPETUATED (See sketch on back)  PATRICAL DESCRIPTION OF MCHUMENTS MEMBLY OR PROPERTIES (See sketch on back)  PATRICAL DESCRIPTION OF MCHUMENTS MEMBLY OR PROPERTIES (See sketch on back)  PATRICAL DESCRIPTION OF MCHUMENTS MEMBLY OR PROPERTIES (See sketch on back)  PATRICAL DESCRIPTION OF MCHUMENTS MEMBLY OR PROPERTIES (See sketch on back)  PATRICAL DESCRIPTION OF MCHUMENTS MEMBLY OR PROPERTIES (SECOND OF THE SECOND OF THE STATION O	<b>T</b>	•					
PAYRICAL DESCRIPTION OF COMMER FOUND, EVIDENCE AND METHOD USED TO IDENTIFY OF RETSTABLISH FOUND AND ACCEPTED: A 1" O.D.I.P., 24" long, up 7", tagged RCE 21650.  Corner position established by subdivision of section procedure.  (See sketch on back)  PAYRICAL DESCRIPTION OF MONUMENTS REQUIT OF PERFETUATED REMODILIMENT OF MONUMENTS SETTING A COLOR OF THE PROPERTY OF THE PERFETUATED REMODILIMENT OF THE WORST.  FIRST OF THE PERFETUATION OF MONUMENTS OF THE PERFETUATION OF TH	CORNER - LEFT AS FOUND (	POUND AND TAGE	GEO [7] BEESTA	UISHED OBLITERA	TO COPME C	Marine Co	· ·
FOUND AND ACCEPTED: A 1" O.D.I.P., 24" long, up 7", tagged RCE 21650.  Corner position established by subdivision of section procedure.  (See sketch on back)  PHYSICAL DESCRIPTION OF MONUMENTS REMULT OR PENETUATED Remonumented found pipe with F.S.M., up 12". Built a rock mound 3' dia. by 1' high around monument. Set a metal post with Forest Service monument signs attached 4" ± NW of the corner. Buried found monument horizontally on the west side of the F.S.M.  F.S.M Aluminum monument, 2 1/2" O.D., 30" long with a 3 1/4" O.D. aluminum cap stamped for the corner, with LS 4689, the date and the Forest Service logo.  CAUPONIA COORDINATE SYSTEM CROSE. FIRST   SECOND   STATION SIZE   COUNT   OTHER   STATION   STATION    SACHINGS (DY STATION   NOTHINGS (T)   STATION   STATION   STATION    SKETCH: (Include reference fie or wilness points, remarks and topo of areo)  Corner Ties:  1. A White Fir, 15.3" dia., bears N 54°07' E, 42.04'. S 1/16  S 28	PHYSICAL DESCRIPTION OF CO					sesore S	<del></del>
Corner Ties:  1. A White Fir, 15.3" dia., bears N 54°07' E, 42.04'.  See RP.K. nail and tag (LS 4689) in a rock, 8' x 9' x 4'  1. A White Fir, 15.3" dia., bears N 71° 20' 36" W, 58.50'.  2. A P.K. nail and tag (LS 4689) in a rock, 8' x 9' x 4'  2. A P.K. nail and tag (LS 4689) in a rock, 8' x 9' x 4'  2. A P.K. nail and tag (LS 4689) in a rock, 8' x 9' x 4'  3. A chiseled "+" in a rock, 6' x 14' x 7 1/2' high'  bears N 71° 20' 36" W, 58.50'.  Course of the corner of tree at the base. Distance is horizontal to a nail and (stamped LS 4689) driven into the side center of the root crown.  Corner Ties:  Cap Inscription  U-13  F.B. 34/72  Job No. 85-9  Description the corner of tree at the base. Distance is horizontal to a nail and (stamped LS 4689) driven into the side center of the root crown.  Calcally and the corner of the corner of the root crown.  Let Forest Service monument and bearing tree signs.  Cap Inscription 1. S 1/16  S 28  S 27  LS 4689  A P.K. nail and tag (LS 4689) and rock, 8' x 9' x 4'  LS 4689  A P.K. nail and tag (LS 4689) and rock, 8' x 9' x 4'  LS 4689  A P.K. nail and tag (LS 4689) and rock, 8' x 9' x 4'  LS 4689  A P.K. nail and tag (LS 4689) and rock, 8' x 9' x 4'  LS 4689  A P.K. nail and tag (LS 4689) and rock, 8' x 9' x 4'  LS 4689  A P.K. nail and tag (LS 4689) and rock, 8' x 9' x 4'  LS 4689  A P.K. nail and tag (LS 4689) and rock, 8' x 9' x 4'  LS 4689  A P.K. nail and tag (LS 4689) and rock, 8' x 9' x 4'  LS 4689  A P.K. nail and tag (LS 4689) and rock, 8' x 9' x 4'  A P.K. nail and tag (LS 4689) and rock, 8' x 9' x 4'  A P.K. nail and tag (LS 4689) and rock, 8' x 9' x 4'  A P.K. nail and tag (LS 4689) and rock, 8' x 9' x 4'  A P.K. nail and tag (LS 4689) and rock, 8' x 9' x 4'  A P.K. nail and tag (LS 4689) and rock, 8' x 9' x 4'  A P.K. nail and tag (LS 4689) and rock, 8' x 9' x 4'  A P.K. nail and tag (LS 4689) and rock, 8' x 9' x 4'  A P.K. nail and tag (LS 4689) and rock, 8' x 9' x 4'  A P.K. nail and tag (LS 4689) and rock, 8' x 9' x 4'  A P.K. nail and tag (LS 4689) and rock, 8						1650	* *
Remonumented found pipe with F.S.M., up 12". Built a rock mound 3' dia. by 1' high around monument. Set a metal post with Forest Service monument signs attached 4' ± MV of the corner. Buried found monument horizontally on the west side of the F.S.M.  F.S.M Aluminum monument, 2 1/2" O.D., 30" long with a 3 1/4" O.D. aluminum cap stamped for the corner, with LS 4689, the date and the Forest Service logo.  CALICINIA COCIONATE SYSTEM CHOSE. SHATE   SECOND   STATEON   STATE	Corner position est	ablished by sub	division of	section pr	ocedure.	:	·
Remonumented found pipe with F.S.M., up 12". Built a rock mound 3' dia. by 1' high around monument. Set a metal post with Forest Service monument signs attached 4' ± NW of the corner. Buried found monument horizontally on the west side of the F.S.M.  A luminum monument, 2 1/2" O.D., 30" long with a 3 1/4" O.D. aluminum cap stamped for the corner, with LS 4689, the date and the Forest Service logo.  CALMODNIA COCKDINATE SYSTEM ORDER: **IRST   SECOND   THIRD   STATION   STA	(See sketch on back	<u>:)</u>	•	-		·.	
REMONDMENTHER OF COUNTY SURVIVORS CEREBLAND (A)  Remonument the found pipe with F.S.M., up 12". Built a rock mound 3' dia. by 1' high around monument. Set a metal post with Forest Service monument signs attached 4' ± NW of the corner. Buried found monument horizontally on the west side of the F.S.M.  REMONDMENT OF THE COUNTY OF THE STATE OF THE SECOND OF THE STATE OF							
REMONDMENTHER OF COUNTY SURVIVORS CEREBLAND (A)  Remonument the found pipe with F.S.M., up 12". Built a rock mound 3' dia. by 1' high around monument. Set a metal post with Forest Service monument signs attached 4' ± NW of the corner. Buried found monument horizontally on the west side of the F.S.M.  REMONDMENT OF THE COUNTY OF THE STATE OF THE SECOND OF THE STATE OF							
Remonumented found pipe with F.S.M., up 12". Built a rock mound 3' dia. by 1' 4' ± NW of the corner. Burled found monument horizontally on the west sides attached of the F.S.M. 4' ± NW of the corner. Burled found monument horizontally on the west sides of the F.S.M.  Stamped for the corner, with LS 4689, the date and the Forest Service logo.  CAURONNIA COORDINATE SYSTEM CROSES. #HEST   SECOND   THIRD   STATION	PHYSICAL DESCRIPTION OF ME	MINISTE MANUEL CO. SCI.	ACTI A TITO	· .			
high around monument. Set a metal post with Forest Service monument signs attached "+" ± MV of the corner. Buried found monument horizontally on the west side of the F.S.M.  F.S.M Alluminum monument, 2 1/2" O.D., 30" long with a 3 1/4" O.D. aluminum cap stamped for the corner, with LS 4689, the date and the Forest Service logo.  CALIFORNIA COORDINATE SYSTEM ORDER: #HEST   SECOND   THIRD   STATION   S	Remonumented found	pipe with F.S.M	., up 12". B	uilt a roc	k mound 3'	dia. by 1	-
of the F.S.M. — Aluminum monument, 2 1/2" O.D., 30" long with a 3 1/4" O.D. aluminum cap stamped for the corner, with LS 4689, the date and the Forest Service logo.  CALFORNIA COCCUMATE STSTEM QADDE: STATE   SECOND   THISD   STATION   S	high around monumer	it. Set a metal	post with Fo	rest Servi	ce monumen	t signs atta	ched
F.S.M Aluminum monument, 2 1/2" O.D., 30" long with a 3 1/4" O.D. aluminum cap stamped for the corner, with LS 4689, the date and the Forest Service logo.  CALFORNIA COORDINATE SYSTEM ORDER: #1857   SECOND   THIRD   STATION	of the F S M	er. Burled found	d monument h	orizontall	y on the w	est side	
Stamped for the corner, with LS 4689, the date and the Forest Service logo.  CALMORNIA COORDINATE SYSTEM ORDER: FIRST COUNTY COUNTY STATION SYSTEM ORDER: STATION SYSTEM ORDER: STATION SYSTEM ORDER: STATION STATION STATION STATION NORTHINGS (7) PLASTINGS (X)  SKETCH: (Include reference fie or witness points, remarks and topo of area)  Corner Ties:  1. A White Fir, 15.3" dia., bears N 54°07' E, 42.04'. S 1/16  2. A P.K. nail and tag (LS 4689) in a rock, 8' x 9' x 4' LS 4689 high, bears S 18° 20' 54" W, 25.13'. 1985  3. A chiseled "+" in a rock, 6' x 14' x 7 1/2' high! bears N 71° 20' 36" W, 58.50'. U-13 F.B. 34/72 Job No. 85-9  Des run east and south from the corner.  Fring is to the center of tree at the base. Distance is horizontal to a nail and (stamped LS 4689) driven into the side center of the root crown.  The forest Service monument and bearing tree signs.  SUMMEROR SUMMEROR SERUMAN / COMMIT SURVEYOR'S CENTINCARE /		onument. 2 1/2"	O.D. 30# 1	ong with s	3 1/ມາ ሰ ፣	) aliminim	00 D
CAUFORNIA COORDINATE SYSTEM ORDER. FIRST   SECOND   THERD   STATION   STATIO	stamped for the cor	ner, with LS 46	89, the date	and the F	orest Serv	ice logo.	υαρ
STATIONS USED: NGS (USC A GS) STATE COUNTY OTHER STATION STATION STATION NORTHINGS (Y)  SKETCH: (Include reference He or witness points, remarks and topo of area)  Corner Ties:  1. A White Fir, 15.3" dia., bears N 54°07' E, 42.04'. S 1/16 S 28 S 27 LS 4689 high, bears S 18° 20' 54" W, 25.13'.  3. A chiseled "+" in a rock, 6' x 14' x 7 1/2' high bears N 71° 20' 36" W, 58.50'.  3. A chiseled "4" in a rock, 6' x 14' x 7 1/2' high bears N 71° 20' 36" W, 58.50'.  3. A chiseled "4" in a rock, 6' x 14' x 7 1/2' high bears N 71° 20' 36" W, 58.50'.  3. A chiseled "4" in a rock, 6' x 14' x 7 1/2' high bears N 71° 20' 36" W, 58.50'.  3. A chiseled "4" in a rock, 6' x 14' x 7 1/2' high bears N 71° 20' 36" W, 58.50'.  3. A chiseled "4" in a rock, 6' x 14' x 7 1/2' high bears N 71° 20' 36" W, 58.50'.  3. A chiseled "4" in a rock, 6' x 14' x 7 1/2' high bears N 71° 20' 36" W, 58.50'.  3. A chiseled "4" in a rock, 6' x 14' x 7 1/2' high bears N 71° 20' 36" W, 58.50'.  4. U-13 5. F.B. 34/72 5. Job No. 85-9  The station of the corner of the root crown.  5. See From the corner of the root crown.  6. See Forest Service monument and bearing tree signs.  6. See From the corner of the root crown.  6. See From the corner of the root crown.  6. See From the corner of the root crown.  6. See From the corner of the root crown.  6. See From the corner of the root crown.  6. See From the corner of the root crown.  6. See From the corner of the root crown.  6. See From the corner of the root crown.			<del></del>				
SKETCH: (Include reference fie or witness points, remarks and topo of area)  Corner Ties:  1. A White Fir, 15.3" dia., bears N 54°07' E, 42.04'.  2. A P.K. nail and tag (LS 4689) in a rock, 8' x 9' x 4' high, bears S 18° 20' 54" W, 25.13'.  3. A chiseled "+" in a rock, 6' x 14' x 7 1/2' high' bears N 71° 20' 36" W, 58.50'.  3. A chiseled The interpretation of the corner.  Ting is to the center of tree at the base. Distance is horizontal to a nail and (stamped LS 4689) driven into the side center of the root crown.  Ting is to the center of tree at the base. Distance is horizontal to a nail and (stamped LS 4689) driven into the side center of the root crown.  Ting is to the center of tree at the base. Distance is horizontal to a nail and (stamped LS 4689) driven into the side center of the root crown.  Ting is to the center of tree at the base. Distance is horizontal to a nail and (stamped LS 4689) driven into the side center of the root crown.  Ting is to the center of tree at the base. Distance is horizontal to a nail and (stamped LS 4689) driven into the side center of the root crown.  Ting is to the center of tree at the base. Distance is horizontal to a nail and (stamped LS 4689) driven into the side center of the root crown.  The surveyors content and bearing tree signs.						STATION	
Cap Inscription  1. A White Fir, 15.3" dia., bears N 54°07' E, 42.04'.  2. A P.K. nail and tag (LS 4689) in a rock, 8' x 9' x 4' high, bears S 18° 20' 54" W, 25.13'.  3. A chiseled "+" in a rock, 6' x 14' x 7 1/2' high' bears N 71° 20' 36" W, 58.50'.  4. B. 34/72 Job No. 85-9  The run east and south from the corner.  Ting is to the center of tree at the base. Distance is horizontal to a nail and (stamped LS 4689) driven into the side center of the root crown.  The run east service monument and bearing tree signs.  The run east service monument and bearing tree signs.  The run east service monument and bearing tree signs.  The run east service monument and bearing tree signs.			_		PASTIN	GS (X)	
Cap Inscription  1. A White Fir, 15.3" dia., bears N 54°07' E, 42.04'.  2. A P.K. nail and tag (LS 4689) in a rock, 8' x 9' x 4' high, bears S 18° 20' 54" W, 25.13'.  3. A chiseled "+" in a rock, 6' x 14' x 7 1/2' high' bears N 71° 20' 36" W, 58.50'.  4. B. 34/72 Job No. 85-9  The run east and south from the corner.  Ting is to the center of tree at the base. Distance is horizontal to a nail and (stamped LS 4689) driven into the side center of the root crown.  The run east service monument and bearing tree signs.  The run east service monument and bearing tree signs.  The run east service monument and bearing tree signs.  The run east service monument and bearing tree signs.	SKETCH: (Include reference	tie or witness points					,
1. A White Fir, 15.3" dia., bears N 54°07' E, 42.04'.  2. A P.K. nail and tag (LS 4689) in a rock, 8' x 9' x 4' high, bears S 18° 20' 54" W, 25.13'.  3. A chiseled "+" in a rock, 6' x 14' x 7 1/2' high bears N 71° 20' 36" W, 58.50'.  3. Es 4689 F.B. 34/72 Job No. 85-9  Des run east and south from the corner.  Ting is to the center of tree at the base. Distance is horizontal to a nail and (stamped LS 4689) driven into the side center of the root crown.  The forest Service monument and bearing tree signs.  Tamped monument in accordance with the BLM 1973 " Manual of Surveying Instructions".	•	ne or williess points, ren	idika dha lopo of a	r <del>eo</del> )			
2. A P.K. nail and tag (LS 4689) in a rock, 8' x 9' x 4' high, bears S 18° 20' 54" W, 25.13'.  3. A chiseled "+" in a rock, 6' x 14' x 7 1/2' high' bears N 71° 20' 36" W, 58.50'.  U-13 F.B. 34/72 Job No. 85-9  Des run east and south from the corner.  ring is to the center of tree at the base. Distance is horizontal to a nail and (stamped LS 4689) driven into the side center of the root crown.  The Forest Service monument and bearing tree signs.  SURVEYOR'S CHEMICATE (COUNTY SURVEYOR'S COUNTY SURVEYOR'S CHEMICATE (COUNTY SURVEYOR'S C	corner ries:				Cap Ir	scription	
S 28 S 27 LS 4689 high, bears S 18° 20' 54" W, 25.13'.  3. A chiseled "+" in a rock, 6' x 14' x 7 1/2' high' bears N 71° 20' 36" W, 58.50'.  3. Es 4689 Hears N 71° 20' 36" W, 58.50'.  4. The content of the corner.  4. The content of the corner of the corner of the root crown.  5. The content of the content of the root crown.  6. The content of the corner of the root crown.  6. The corner of the root crown.	I. A White Fir, 15.	3" dia., bears i	N 54 <sup>0</sup> 07' E.	12.041.	s	1/16	è
A chiseled "+" in a rock, 6' x 14' x 7 1/2' high bears N 71° 20' 36" W, 58.50'.  U-13 F.B. 34/72 Job No. 85-9  es run east and south from the corner.  ing is to the center of tree at the base. Distance is horizontal to a nail and (stamped LS 4689) driven into the side center of the root crown.  ed Forest Service monument and bearing tree signs.  mped monument in accordance with the BLM 1973 " Manual of Surveying Instructions".		· · · · · · · · · · · · · · · · · · ·			S 28		
B. A chiseled "+" in a rock, 6' x 14' x 7 1/2' high bears N 71° 20' 36" W, 58.50'.  U-13 F.B. 34/72 Job No. 85-9  The ses run east and south from the corner.  Fing is to the center of tree at the base. Distance is horizontal to a nail and (stamped LS 4689) driven into the side center of the root crown.  The second recommendate with the BLM 1973 " Manual of Surveying Instructions".  The second recommendate with the BLM 1973 " Manual of Surveying Instructions".	A P.K. nail and	tag (LS 4689) ir	n a rock, 8º	x 91 x 41	LS		
bears N 71° 20° 36° W, 58.50°.  U-13 F.B. 34/72 Job No. 85-9  The session of the corner.  The session of the corner of the corner of the control of the control of the control of the root crown.  The session of the corner of the corner of the root crown.  The session of the corner of the root crown.  The session of the corner of the root crown.  The session of the corner of the root crown.  The session of the corner of the root crown.  The session of the corner of the root crown.  The session of the corner of the root crown.  The session of the corner of the root crown.	nign, bears S 18	20' 54" W, 25.	131.	•		1985	
bears N 71° 20° 36° W, 58.50°.  U-13 F.B. 34/72 Job No. 85-9  The session of the corner.  The session of the corner of the corner of the control of the control of the control of the root crown.  The session of the corner of the corner of the root crown.  The session of the corner of the root crown.  The session of the corner of the root crown.  The session of the corner of the root crown.  The session of the corner of the root crown.  The session of the corner of the root crown.  The session of the corner of the root crown.  The session of the corner of the root crown.	. A chiseled "+" i	n a rock. 6t x 1	141 x 7 1/21	hight			
F.B. 34/72 Job No. 85-9  ses run east and south from the corner.  ring is to the center of tree at the base. Distance is horizontal to a nail and (stamped LS 4689) driven into the side center of the root crown.  ed Forest Service monument and bearing tree signs.  mped monument in accordance with the BLM 1973 " Manual of Surveying Instructions".	bears N 710 20'	36" W, 58.50'.	, x , 1/2	111811	U <b>–1</b> 3		
ces run east and south from the corner.  ring is to the center of tree at the base. Distance is horizontal to a nail and (stamped LS 4689) driven into the side center of the root crown.  ted Forest Service monument and bearing tree signs.  amped monument in accordance with the BLM 1973 " Manual of Surveying Instructions".	•	·		-		'2	
ring is to the center of tree at the base. Distance is horizontal to a nail and (stamped LS 4689) driven into the side center of the root crown.  The communication of tree at the base. Distance is horizontal to a nail and stamped LS 4689) driven into the side center of the root crown.  The communication of tree at the base. Distance is horizontal to a nail and stamped LS 4689) driven into the side center of the root crown.  The communication of tree at the base. Distance is horizontal to a nail and stamped LS 4689) driven into the side center of the root crown.  The communication of the root crown.	•				Job No. 8	85-9	-
ring is to the center of tree at the base. Distance is horizontal to a nail and (stamped LS 4689) driven into the side center of the root crown.  The common state of tree at the base. Distance is horizontal to a nail and stamped LS 4689) driven into the side center of the root crown.  The common state of tree at the base. Distance is horizontal to a nail and stamped LS 4689) driven into the side center of the root crown.  The common state of tree at the base. Distance is horizontal to a nail and stamped LS 4689) driven into the side center of the root crown.  The common state of the root crown.  The common state of the root crown.	es min east and so	ith from the cor	nor	,	* .		
(stamped LS 4689) driven into the side center of the root crown.  Led Forest Service monument and bearing tree signs.  Imped monument in accordance with the BLM 1973 " Manual of Surveying Instructions".	ob tan cabo and bot	ADIT TO OIL DIE COL	net •				
(stamped LS 4689) driven into the side center of the root crown.  ted Forest Service monument and bearing tree signs.  amped monument in accordance with the BLM 1973 " Manual of Surveying Instructions".	ring is to the cent	er of tree at th	ne base. Dist	ance is h	orizontal t	o a nail and	
surveyors current AND S	(stamped LS 4689)	iriven into the	side center	of the roo	ot crown.		
suavevors country Suavevors CHIDAGO	ted Forcet Service :	nonimont and bec		· •			
SURVEYOR'S CHANGE OF LAND SUS COUNTY SURVEYOR'S CHANGE /	red totest penatce i	monument and bea	ring tree si	.gns.	-		
SURVEYOR'S CHAND SUS COUNTY SURVEYOR'S CHANDERS (	amped monument in ac	cordance with t	he BLM 1973	" Manual d	of Survevin	g Instructio	ns#
THIS CORNER RECORD WAS PRESEND BY ME OR UNDER AND THE CORNER RECORD WAS RECEIVED 10-31 1						P THOU WOULD	110
THIS CORNER RECORD WAS PRESENTED AT ME OR UNDER A THE CORNER RECORD WAS RECEIVED 10-31	1.		· ·		·	<u> </u>	
THIS CORNER RECORD WAS PRESENT AT HE OR UNDERLINE THE CORNER RECORD WAS RECEIVED 16-31	SURYEYO	rs quite DaLANU S	Val		COUNTY SURVI	TOR'S CIRTIFICATE	1
TOTAL TOTAL CONTRACTOR OF THE PARTY OF THE P		MAY I				\$10 10-34	1085
ON SCHOOL OF THE WAND SHANDER AND EXAMINED A	Sat-line	THO WAYD HAND	13. A. 22	AND EXAMIN	ED AND PICED	11/1	10

West 14 cor. Sec. 27 5/23

Found rock md & 2

Orig. BT's. Remonumented

With F.S.M., up 3" in

a rock md. M.C.C.R.

S 416 Cor. Sec. 27 5/23

. .

No scale

SW Can

SIN Cor. Sec. 27 5/23.
Found 14 0.1.P.,
LS. 4727 in rock md.
\$ 2 orig. BT's
Remonumented with
F.S. M., up 8" in a rock
md. M.C.C.R.