CORNER	RECORD
COUNTY OF MADERA TOWNSHIP 5 SOUTH, RAN	GE 23 EAST, M.D.B.&M. CALIFORNIA
CORNER TYPE: GOV'T. CORNER MEANDER	rancho Control Other C
CORNER IDENTIFICATION - DATE OF VISIT: June	19_81_
North 4 corner of	
CORNER - LEFT AS FOUND FOUND AND TAGGED REEST	
PHYSICAL DESCRIPTION OF CORNER FOUND: EVIDENCE AND METH	OD USED TO IDENTIFY OR REESTABLISH
Found 2'x2'x1' High rock	mound
PHYSICAL DESCRIPTION OF MONUMENTS REBUILT OR PERPETUATE	D
	•
CALIFORNIA COORDINATE SYSTEM ORDER: FIRST	and the second s
·	
STATIONS USED: NGS (USC & GS) STATE	
ZONE ELEVATION NORTH:	INGS (Y)EASTINGS (X)
SKETCH: (INCLUDE REFERENCE TIE OR WITNESS POINTS, REMARK	(S AND TOPO OF AREA)
TIES	
45" Jeffrey Pine be	ars S 12° E 27.1'
52" Jeffrey Pine be	ars N 20° W 48.2'
On center of rock r	idge 330' East of road
Copied from Parcel map Surveyed by Joe Smyth R	
SURVEYOR'S CERTIFICATE	COUNTY SURVEYOR'S CERTIFICATE
THIS CORNER RECORD WAS PREPARED BY ME OR UNDER MY DIRECTION IN CONFORMANCE WITH THE LAND SURVEYOR'S	THE CORNER RECORD WAS RECEIVED 19
ACT ON 19	AND EXAMINED AND FILED
	BY:
SIGNED:	TITLE:
L.S. or R.C.E. No:	

SEAL

DOCUMENT NO: STATEMENT ON BACK OF SHEET:

NO 🗌

·		COR	NER RECORD	·	•
COUNTY OF	Madera	<u>5 S.</u>		1.D.B. & M. MERIDIAN	CALIFORNIA
CORNER IDENTI	GOVT. CORNER 🔀	MEANDER RANCI	19 CONTROL []	отива 🗀	
			- · ·		
	- ine nort	th 1/4 corner of s	section 34 5/23.		
	·				
CORNER - LEFT	AS FOUND	POUND AND TAGGED	REESTABLISHED OBLITERA	TEN CORNER CO.	· · · · · · · · · · · · · · · · · · ·
PHTSICAL DESCI	HIPTION OF COUNER	FOUND: EVIDENCE AND MET	HOD USED TO IDENTIFY OF	Distriction	
LOUND AND	AUCEPTED: A	3' dia x 1/2'	high rock mound	and 2 ontertact hearts	g
crees ber	iterd notes	of J.M. Anderson,	U.S. Deputy Sur	veyor, 1881.	-
		en e			
PHYSICAL DESCR	IFTION OF MONUME	NTS REBUILT OR PERPETUATED			
Remondinent	ed rock mound	a with F.S.M., in	77 Rebuilt wool	k mound 3' dia. by 8"	
	the corner.	Set a metal post v	with Forest Serv	ice monument signs att	cached
stamped for	r the corner	nent, 2 1/2" 0.D.,	, 30" long with a	a 3 1/4" O.D. aluminum Forest Service logo.	cap
				orest Service logo.	
STATIONS USED:	ORDINATE SYSTEM OR INGS (USC & GS)			STATION	
ZONE	- ELEVATION	NORTHINGS	_ —	STATIONSTATIO	×
SKETCH: (Inclu	de reference tie or	witness points, remarks and	topo of area)		
ner Ties:		- Tremera Gild	topo or dreat	_	
	_			Cap Inscription	
<u>Original Be</u>	earing Trees:			T 5 S R 23 E	
1. A Ponder	osa Pine 50	dia., bears N 20	⁰ 33' W. 48.7'.	S 27 1/4	*.
(no nai]		T		S 34	
2. A pine s	snag 45" dia.	, bears S 13 ⁰ 26'	E. 28.91	LS 4689 1985	
(no nail	.)		1, 20, ,	1305	•
NEW BEARING	OBJECTS:	,			
1. A Ponder	osa Pine, 11	.3" dia., bears N	56° 13' E, 68.9	5 '.	**
2. A Ponder	osa Pine, 42	.1" dia., bears S	13° 56' W. 76.09)1_	•
				77	15
N 87 ⁰ 48	* 25" W, 40.9	(LS 4689) in rock	20'x20'x12' high		
	,			Job No. 85- (Continued on ba	
r		GED LAND SU			· · · · · · · · · · · · · · · · · · ·
	SURVEYOR	hereare		COUNTY SURVEYOR'S CIRTIFICATE	7
THIS CORNER R	CORD WAS FREELE	THE LANGUE VETOES ACT		SCORD WAS PROTEIVED	13/10/85
OH	close 9	1923	AND EXAMINE	BY AMBELLA	Tuson
SIGNE	o Haward	arnold low]	mari	
L1 MANGE N	444	74/	DOCUMENT N	·	
	N c	LS 4689	STATEMENT ON	SACK OF SHEET	
		E OF TALKS			
the second section of the second sections	A SECTION AND CONTRACT OF THE SECTION ASSESSMENT	The same of the sa		•	

4. A chiseled cross "+" in the top center of a rock 8'x18'x3 1/2'high, bears N 07 20' 17" E, 66.93'.

Bearings are to the center of trees at the base. Distances are horizontal to a nail and tag (stamped LS 4689) driven into the side center of the root crown, unless otherwise noted.

Posted Forest Service monument and bearing tree signs.

Stamped monument in accordance with the BLM 1973 " Manual of Surveying Instructions".

