	CORNER RECORD		
	COUNTY OF MADERA T. 5 S.		
	CORNER TYPE: GOVT. CORNER MEANDER RANGE CORNER IDENTIFICATION — DATE OF VISIT NOVEMBER	HO CONTROL OTHER	
	CORNER IDENTIFICATION — DATE OF VISITNILY GUILLED	: 	
	west 1/4 corner section 13		
	CORNER — LEFT AS FOUND TO FOUND AND TAGGED TO REESTABLISHED OBLITERATED CORNER TO REBUILT TO		
	PHYSICAL DESCRIPTION OF CORNER FOUND, EVIDENCE AND METHOD USED TO IDENTIFY OR REESTABLISH		
$\mathbf{F}c$	ound 24" dia. Lodgepole Pine bla	zed on four sides and one	
origi	inal bearing tree, per gov't. no		
	on to sections 13 and 14.		
N			
,			
	PHYSICAL DESCRIPTION OF MONUMENTS REBUILT OR PERPETUATED		
<b>ವ</b>	et witness corner on section lin	e South, 25.00 dist. S 00 32 43 E	
Set 2	dia. Aluminum pipe, 25" long	with 3 1/4" Aluminum cap stamped	
"L.S.	"L.S. 3670- 1978", up 8" in mound of dirt.		
	CALIFORNIA COORDINATE SYSTEM ORDER: FIRST SECOND THIRD STATION		
	SKETCH: (include reference tie or witness points, remarks an	d tapo of area)	
	TIES TO WITNES	S CORNER :	
N 07.5	45' E , 49.28' Set nail and was	sher stempe <b>&amp;</b> "L.S. 3670" at	
M OV	base of 22 dia	Lodgepole Pine, on right side.	
		, word ober a rue; ou ruero prace;	
ท 78 ั		sher stamped "L.S. 3670" at	
	base of 24" dia.	Lodgepole Pine, on right side.	
C 74°	451 F 56 761 Oct mot 3 and 450	There of the second the second the second	
<b>3</b> 34	45' E , 56.76' Set nail and was	sher stamped "L.S. 3670" at	
	base of 21 dia	. Lodgepole Pine, on right side.	
<b>s</b> 02°	15' W . 48.42' Set nail and Was	sher stamped "L.S. 3670" at	
		Lodgepole Pine, on right side.	
0		•	
N 50	50°00' W , 4.62' Set nail and washer stamped "L.S. 3670" at		
	Dase of 25" dia.	. Lodgepole Pine, on right side.	
NOTE:	Copied from Record of Survey for	or Southern California Edison Co.	
- 1	by Robert S. Hodson L.S. 3670		
THIS CORNER RECORD WAS PREPARED BY ME OR UNDER MY THE CORNER RECORD WAS		COUNTY SURVEYOR'S CERTIFICATE	
	ON	BY.	
	•	WTLE;	
	SIGNED:	DOCUMENT No.	
	L.O. DI N.C.D. 1704	· •	

STATEMENT ON BACK OF SHEET