

NOTE: Copied from Record of Survey for Southern California Edison Co.  
by Robert S. Hodson L.S. 3670

**CORNER RECORD**

COUNTY OF MADERA T. 5 S. R. 24 E. M.D.B. & MERIDIAN CALIFORNIA  
 CORNER TYPE: GOVT. CORNER  MEANDER  RANCHO  CONTROL  OTHER   
 CORNER IDENTIFICATION — DATE OF VISIT November 19 78



NORTHWEST CORNER SECTION 26

CORNER — LEFT AS FOUND  FOUND AND TAGGED  REESTABLISHED OBLITERATED CORNER  REBUILT

PHYSICAL DESCRIPTION OF CORNER FOUND; EVIDENCE AND METHOD USED TO IDENTIFY OR REESTABLISH

Found 3' dia. rock mound 1' high and four original bearing trees, per gov't. notes. Accepted as corner common to sections 22, 23, 26 and 27.

PHYSICAL DESCRIPTION OF MONUMENTS REBUILT OR PERPETUATED

Set 2" dia. Aluminum pipe, 25" long with 3 1/4" Aluminum cap stamped "L.S. 3670 - 1978", up 8" in center of found rock mound.

CALIFORNIA COORDINATE SYSTEM ORDER: FIRST  SECOND  THIRD   
 STATIONS USED: NGS (USC & GS)  STATE  COUNTY  OTHER  STATION \_\_\_\_\_ STATION \_\_\_\_\_  
 ZONE \_\_\_\_\_ ELEVATION \_\_\_\_\_ NORTHINGS (N) \_\_\_\_\_ EASTINGS (E) \_\_\_\_\_

SKETCH: (Include reference tie or witness points, remarks and topo of area)

- N 67° 41' E , 60.30' Original bearing tree found to be 36" dia. Lodgepole Pine with open blaze 8" deep. "SXXIII B.T." visible and in good condition.
- S 04° 34' E , 82.30' Original bearing tree found to be 42" dia. Lodgepole Pine with open blaze 9" deep. "SXXVI B.T." visible and in good condition.
- S 45° 19' W , 56.00' Center of rotten stump, possible Southwest bearing tree.
- N 10° 39' W , 39.00' Original bearing tree found to be 44" dia. Lodgepole Pine with no blaze visible.
- N 37° 45' E , 40.44' Set nail and washer stamped "L.S. 3670" at base of 4" dia. Lodgepole Pine, on right side.
- N 81° 45' E , 9.85' Set nail and washer stamped "L.S. 3670" at base of 10" dia. Lodgepole Pine, on right side.
- S 03° 15' E , 8.34' Set nail and washer stamped "L.S. 3670" at base of 6" dia. Lodgepole Pine, on right side.
- S 59° 30' W , 13.28' Set nail and washer stamped "L.S. 3670" at base of 11" dia. Lodgepole Pine, on right side.
- N 15° 15' W , 31.69' Set nail and washer stamped "L.S. 3670" at base of 13" dia. Lodgepole Pine, on right side.
- S 31° 30' W , 1.48' Set nail and washer stamped "L.S. 3670" on top of 18" dia. Lodgepole Pine stump on right side.

**SURVEYOR'S CERTIFICATE**  
 THIS CORNER RECORD WAS PREPARED BY ME OR UNDER MY DIRECTION IN CONFORMANCE WITH THE LAND SURVEYORS ACT ON \_\_\_\_\_ 19\_\_\_\_\_  
 SIGNED: \_\_\_\_\_  
 L.S. or R.C.E. No.: \_\_\_\_\_

SEAL

**COUNTY SURVEYORS CERTIFICATE**  
 THE CORNER RECORD WAS RECEIVED \_\_\_\_\_ 19\_\_\_\_\_  
 AND EXAMINED AND FILED \_\_\_\_\_ 19\_\_\_\_\_  
 BY: \_\_\_\_\_  
 TITLE: \_\_\_\_\_  
 DOCUMENT No. \_\_\_\_\_  
 STATEMENT ON BACK OF SHEET YES  NO