

Index File No. _____

CORNER RECORD (SEARCH)
(Ref. FSM 7151.4)

Tract or Survey No. _____

20

Cor. No. S14 Sec 11

T 6S R. 20E

R.D. _____


County Marquette

Merid. M.D.B. & M.

N.F. Sierra

State MI


CORNER DIAGRAM



DESCRIBE CORNER MONUMENT FOUND

Found 9" charred fence corner post with scattered rocks at base. Fence to East, West and South. Post fits BLC top calls to west. Position fits that shown on 1977 Marquette Co. Record of Survey Map No. 18-110 by RFE 21650 relative to other monuments. Accepted as perpetuation of original corner monument.

DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND original corner monument.
1. No original bearing trees found.



2. Fits BLC top calls to west.

DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER

From Highway 49 follow USFS Road 6379 1.5 miles ± to a gate and posted line. Follow posted line westerly for 2000' ± to corner, at fence corner.

PHOTO IDENTIFICATION DATA

Photo No. _____
Filed At. _____
Object Ident. _____
Ident. By _____
Signature _____

PLANE COORDINATE POSITION DATA

State _____ Zone _____
X _____
Y _____
Estab. By _____
Agency _____

Signature [Signature] Title LS 5339 Division _____ Headquarters _____ Date 10/21/90 FS-7100-52 (3/68)

CORNER RECORD (PERPETUATION)

MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT

Set 2 standard USFS aluminum reference monuments, 2 1/2" OD x 30" diameter caps.

Marked!

T6S R20E

1/4 S11 / S14

545°W 10.60

LS 5339 1990

T6S R20E

1/4 S11 / S14

545°E 10.60

LS 5339 1990

ACCESSORIES: DESCRIBE NEW BTL WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE

- 1. A 7" live Oak, blazed and scribed "NBT" bears N83°19'E 38.63'
- 2. Set a metal post with 54-5 and 54-9 signs 545°W 4' from corner post.

Work Done By R. Sieman Title LS Date 10/18/90 State Registration No. 5339 of Agency _____

Certified Cor. Record Prepared? Yes (No) Filed At: _____ Date _____

REMARKS

Bearings are to the center of trees, distances are horizontal to a nail and tag LS 5339 driven into the side center of the root crown. Posted USFS 54-3 and 54-9 signs on all trees. Attached 54-9 sign to corner post.

ex File No. _____ T. _____ R. _____ M. _____ Tract or Surv. No. _____ Cor. _____