

Index File No. _____

CORNER RECORD (SEARCH)
(Ref. FSM 7151.4)

Tract or Survey No. _____

Cor. No. SW Sec. 12

T 6S R. 20E

R.D. _____


County Marquette

Merid. N.D.B. 97N

N.F. Siema

State MI

CORNER DIAGRAM



DESCRIBE CORNER MONUMENT FOUND

Nothing found

DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND

Nothing found

PHOTO IDENTIFICATION DATA

Photo No. _____

Filed At _____

Object Ident. _____

Ident. By _____

Signature

PLANE COORDINATE POSITION DATA

State _____ Zone _____

X _____

Y _____

Estab. By _____

Agency

Signature

Title LS 5339

Division _____

Headquarters _____


Date 10/2/78

FS-7100-52 (3/68)

CORNER RECORD (PERPETUATION)

UMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT

T6S R20E



LS 5339 1990

Set a standard USFS aluminum monument 2 1/2" O.D. x 36" long with marked: a 3 1/2" diameter cap on a rock mound at position established by double proportional measurement

ACCESSORIES: DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE

1. A 12" oak, blazed and scribed "NBT" bears N25°42'W 27.64'
2. A 15" oak, blazed and scribed "NBT" bears N57°32'E 50.92'
3. A 14" pine, blazed and scribed "NBT" bears N88°46'E 51.79'
4. Set a post with 54-5 and 54-9 signs S45°W 4' from monument.

Work Done By R. Seaman Title LS

Date 10/2/78

State Registration No. or Agency 5339

Certified Cor. Record Prepared? Yes No

Filed At _____

Date _____

REMARKS

Bearings are to the center of trees, distances are horizontal to a nail and tag LS 5339 driven into the side center of the root crown. Posted USFS 54-3 and 54-9 signs on all trees.

Index File No. _____

T. _____

R. _____

M. _____

Tract or Surv. No. _____

Cor. _____