CORNER RECORD		
countr of <u>Madera</u> T. 68 R. 21E		MERIDIAN CALIFORN
CORNER TYPE: GOVT. CORNER A MEANDER RANCHO CORNER IDENTIFICATION - DATE OF VISIT April 11	CONTROL OTHER [	
N 1/4 corner Section II with	nin Sierra National Fo	orest.
CORNER — LEFT AS FOUND   FOUND AND TAGGED   REESTA	ABLISHED OBLITERATED CORNER	REBUILT [X]
PHYSICAL DESCRIPTION OF CORNER FOUND; EVIDENCE AND METHOD USES		(A)
Found 3' dia. rock mound 1' high (not original) Found 27" dia. Black Oak w/healed blaze S69½°E (24.4')). Found 60" + Yellow Pine snag N63°W 8' + (60" di	24.2' (24" dia. Black	
PHYSICAL DESCRIPTION OF MONUMENTS REBUILT OR PERPETUATED		
Set 30" aluminum monument with flared base and logo; stamped for corner per BLM Manual of Surv Monument up 8" in center of 3' dia. rock mound. Reset monument at center of rock mound.	eying instructions, d	
CALIFORNIA COORDINATE SYSTEM ORDER: FIRST SECOND	THIRD _	
STATIONS USED: NGS (USC & GS) STATE COUNTY	_	STATION
ZONE ELEVATION NORTHINGS (Y)	EASIR	iGS (X)
SKETCH: (Include reference tie or witness points, remarks and topo of	area)	·
Ties from corner: $869\frac{1}{2}$ OE 24.2' to nail in base of 27" dia. Black $822\frac{1}{4}$ OW 12.6' to nail in base of $4\frac{1}{2}$ " dia. Cedar. $855$ OE 29.7' to nail in base of $10$ " dia. Pondero $840\frac{1}{2}$ OE 8.35' to nail in base of $5\frac{1}{2}$ " dia. Cedar.	sa Pine.	
NOTE: (a) ( ) enclose original survey beari (b) Tie bearings are magnetic with 170 d	ngs and distances.	
(c) Corner location is in agreement with dated 1937.		er tags and records
	•	•
SURVEYOR'S CERTIFICATE  THIS CORNER RECORD WAS PREPARED BY ME OR UNDER MY DIRECTION IN CONFORMANCE WITH THE LAND SURVEYORS ACT ON April 11 19 79		SEIVED APRIL 24 19 79 Seived 19 79 Seived 19 79

DOCUMENT No.

STATEMENT ON BACK OF SHEET