CORNER RECORD		
COUNTY OF Madera T. 6S & 21 & 22 E M.D.B. & MESICIAN CAUPORNI		
CORNER TYPE: GOYT. CORNER WEAHDER REANCHO CORNER IDENTIFICATION - DATE OF VISIT March 16	CONTROL OTHER C	
Northwest corner Section 30		
(Common to Section 24 and 2	25. 6/21 and 19 and 30, 6/22)	
CORNER — LEFT AS FOUND FOUND AND TAGGED	REESTABLISHED OBLITERATED CORNER REBUILT	
Found and Accepted: A 1" O.D., I.P.; 30" long, up 3" above rock mound, 2 1/2' at the base and 1/2' high. Pipe is untagged. Found possible remains of 1 original bearing tree per survey of Archibald McNeil in 1858. This monument is locally recognized and appears on many survey plats filed in Madera County Records, and is accepted as the best available evidence of the original corner position.		
PHYSICAL DESCRIPTION OF MONUMENTS RESULT OR PERPETUATED		
Remonumented with F.S.M., up 9". Placed fo	und pipe inside of F.S.M.	
Built a rock mound 3' at the base and 1' high around monument. Set a metal post with a Forest Service K-tag and attention sign 4'+ N of the monument. F.S.M Aluminum monument, 2-1/2" O.D., 30" long with a 3-1/4" O.D. aluminum cap; stamped for the corner, with LS 4689, the date and the Forest Service logo.		
CALIFORNIA COORDINATE SYSTEM ORDER: FIRST SECO	OND THIRD	
STATIONS USED: NGS (USC & GS) STATE COUNTY ZONE ELEVATION NORTHINGS (T) .	OTHER STATION STATION	
SKETCM: (Include reference tie or witness points, remarks and tops Corner Ties		
	Cap Inscription	
1) A forked Black Oak (5 forks), 20.1" dia, be E.; 39.93'. Note: Diameter, bearing, and o	13.	
to the SE Fork,	6.07	
2) A Ponderosa Pine, 13.4" dia., bears S 3° 39	9' E; 44.02'.	
3) A chiseled '+' in a large rock outcrop, bes 53' 59" W; 76.20'.	, ,	
4) A Chiseled '+' in a large rock outcrop, bea 01" W; 113.47'.	LS 4689 ars N 33° 22' 1983	
5) An old nail and shiner on top of a rock 6' bears N 70° 18' 13"W; 97.05'.		
6) A depression, 5' dia., bears N 26° 57' W; 8 Pine, 16" dia. N 23 1/2° W; 117 1ks (77')). Corner lies N 88° 25' 14" E; 2657.24' fro S. 25,6/21.	· ·	
An intermittent creek flowing S. 25° W, 1	ies 21! West of company	
• All intermittent creek flowing S. 25° W. 1	· All intermittent creek flowing S. 25° W. lies 37' North of corner	
· bearings are to the center of trees at ba	se. Distances are	
horizontal to a nail and tag (stamped LS		
Strucker of the root crown. Strucker of the root crown. Blazer and Service Monument and Bear scribed trees and stamped monument the Blazer Manual of Surveying Instruction.	ing Tree signs. ment in accordance with tions." R-1 2-33	
MOWAMO AMMOLD CAMPICATE	COUNTY SURVEYOR'S CIRTIFICATE	
THIS STRIKER ZECTORD WAS PREPARED BY ME OR UNDER MY	THE CORNER SECOND WAS RECEIVED 19	
ON Asral 6 1983	AND EXAMINED AND HER	
LS 4689 SIGNED: Howard County Column	TITLE:	
	DOCUMENT No.	
E DE CALLO	STATEMENT ON BACK OF SHEET	