


CORNER RECORD

COUNTY OF Madera T. 6 S. R. 22 E. M.D.B. & M. MERRIDIAN CALIFORNIA

CORNER TYPE: GOVT. CORNER MEANDER RANCHO CONTROL OTHER

CORNER IDENTIFICATION - DATE OF VISIT March 26 1984



The southwest corner of section 32 6/22.
(common to sections 31 and 32 6/22)

CORNER - LEFT AS FOUND FOUND AND TAGGED REESTABLISHED OBLITERATED CORNER RESULT

PHYSICAL DESCRIPTION OF CORNER FOUND; EVIDENCE AND METHOD USED TO IDENTIFY OR REESTABLISH

Found and Accepted: A 1 1/2" O.D. iron pipe, up 8", with a 2" dia. brass cap stamped for the corner, the date and the GLO logo. Found 1 bearing tree per GLO field notes of A.W. Brown, U.S. Deputy Surveyor, 1917, and 2 original bearing trees per field notes of Archibald McNeill, U.S. Deputy Surveyor, 1858.

PHYSICAL DESCRIPTION OF MONUMENTS RESULT OR PERPETUATED

Left the monument as found.
Set a metal post with Forest Service monument signs attached, 4' ± SE of the corner.

CALIFORNIA COORDINATE SYSTEM ORDER: FIRST SECOND THIRD
STATIONS USED: NGS (USC & GS) STATE COUNTY OTHER STATION _____ STATION _____
ZONE _____ ELEVATION _____ NORTHINGS (Y) _____ EASTINGS (X) _____

SKETCH: (Include reference tie or witness points, remarks and topo of area)

Corner Ties: (Basis of Bearings is magnetic, dec. = 16 1/2° E)

Cap Inscription

Original Bearing Trees:

1. A Black Oak, 31.7" dia., bears N 69° 31' E, 45.5'.
(healed blaze) (No Nail) (1858 BT)
2. A stump hole, 29" dia., bears S 30° 58' E, 46.5'.
(1858 BT)
3. A Black Oak, 10.2" dia., bears N 38° 10' W, 71.71'. (1917 BT)

T 6 S
R 22 E
S 31 | S 32
S 5
T 7 S
1917

New Bearing Trees:

4. A Black Oak, 14.7" dia., bears S 21° 36' E, 13.25'.
5. A Live Oak, 7.9" dia., bears S 51° 56' W, 14.37'.
6. A Live Oak, 11.8" dia., bears N 76° 19' W, 16.61'.

Z-5
F.B. 24/31
Job No. 84-1

(Continued on back)

SURVEYOR'S CERTIFICATE

THIS CORNER RECORD WAS PREPARED BY ME OR UNDER MY DIRECTION IN CONFORMANCE WITH THE LAND SURVEYORS ACT ON _____ 1984

SIGNED: Howard Arnold
L.S. No. LS 4689

COUNTY SURVEYOR'S CERTIFICATE

THE CORNER RECORD WAS RECEIVED 10-11 1986
AND EXAMINED AND FILED 10/22/86
BY: Howard Arnold
TITLE: _____

DOCUMENT No. _____

STATEMENT ON BACK OF SHEET YES NO

Fences run northerly and westerly from the corner.

Bearings are to the center of trees at the base. Distances are horizontal to a nail tag (stamped LS 4689) driven into the side center of the root crown, unless otherwise noted.

Blazed and scribed bearing trees #4 and #5 in accordance with the BLM 1973 "Manual of Surveying Instructions".

Posted Forest Service monument and bearing tree signs on trees #1, #3, #4 and #5.

062220010

