		TO LAND CO
CORNER	RECORD	SSE SURI
COUNTY OF Madera Y 68 241		TOWARD STATES
CORNER TYPE: 60V'T. CORNER S NEAMORR RANCHO CORNER IDENTIFICATION — DATE OF VISIT September 13	SOUTHOL STHER	COHEN Sourced and to
North 1/2 corner section 17 6/24	4• <u></u>	LS 4689
CORNER - LETT AS FOUND FOUND AND TAGGED REE	STABLISHED OBLITERATED CORNE	OF CALIF
PHYSICAL DESCRIPTION OF CORNER FOUND, EVIDENCE AND METHOD US Found no evidence of original corner monument or	ED TO DENTIFY OR REESTABLISH r accessories.	
Corner position reestablished at record distance book 15 of maps, pages 175-179, M.C.O.R.	e along the south lin	e of tract No. 167 in
Direction of the south line of Tract No. 167 de	termined by prolongin	ng line through found
SET: Nail and tag (LS 4689) at corner position	(in force corner nest) - Set one reference
monument, a 1-3/8" 0.D., I.P., 30" long, up 6", from the corner position.	tagged LS 4689, S 45	6 00' 00" E, 2.00"
STATIONS USED - MGS (USC & GS) T STATE COUNTY	OTHER STATION	STATION
TORE SUSPENSION MONTHUES (N)	£ As	
SKETCH (include reference be or witness points, remorks and topo	ंग्री-बरस्द)	
1. A Ponderosa Pine, 16.4" dia., bears S 42° 39 2. A Ponderosa Pine, 6.1" dia., bears S 55° 40° 3. A Ponderosa Pine, 5.9" dia., bears N 72° 11° 4. A Ponderosa Pine, 9.0" dia., bears N 3° 40°	' 29" W, 26.71'. ' 25" W, 3.90'.	
. Fence lines run north and east from corner Bearings and distances measured to a nail and center of the root crown.		9) driven into the sid
 Posted Forest Service Monument and Bearing Tr Blazed and scribed bearing trees No. 1 and 2 BLM 1973 "Manual of Surveying Instructions." 		in accordance with th
		•
		J-7
		2-5
		AVEYDA'S CERTAKATE
THIS CORNER RECERD WAS PREPARED BY ME OR WHILE MY	THE COMMEN RECORD WA	
DIRECTION IN CONTORNANCE WITH THE SAND SURVEYOR'S ACT	OT S	Musica Adduson
Howard Wadd Colon		

STATEMENT ON BACK OF SHEET