


CORNER RECORD

COUNTY OF Madera T. 7 S. R. 21 E. M.D.R. & M. MERIDIAN CALIFORNIA

CORNER TYPE GOVT. CORNER MEANDER RANCHO CONTROL OTHER

CORNER IDENTIFICATION - DATE OF VISIT March 5 1984



The northwest corner of section 35 7/21.
(common to sections 26, 27, 34 and 35)

CORNER - LEFT AS FOUND FOUND AND TAGGED REESTABLISHED OBLITERATED CORNER RESULT

PHYSICAL DESCRIPTION OF CORNER FOUND; EVIDENCE AND METHOD USED TO IDENTIFY OR REESTABLISH

Found: A 2 1/4" O.D. iron pipe, 30" long, lying horizontally on the ground, with a 2 5/8" dia. brass cap, stamped for the corner, "W.O. GENTRY", "LS 2737" and the date. Found 1 original bearing tree per field notes of John A. Benson and James R. Glover, U.S. Deputy Surveyors, 1875. Re-established the corner position at the intersection of record distances from found bearing objects as shown on document no. 74-15-1 filed in Madera County Surveyor's Office.

PHYSICAL DESCRIPTION OF MONUMENTS RESULT OR PERPETUATED

Set a F.S.M.; flush in ground. Built a 1' x 1' x 6" high rock mound around the monument. Buried found iron pipe alongside the monument. Posted Forest Service monument signs on bearing object #10. F.S.M. - aluminum monument, 2 1/2" O.D., 30" long with a 3 1/4" O.D. aluminum cap, stamped for the corner, with LS 4689, the date and the Forest Service logo.

CALIFORNIA COORDINATE SYSTEM ORDER: FIRST SECOND THIRD
 STATIONS USED: NGS (USC & GS) STATE COUNTY OTHER STATION _____ STATION _____
 ZONE _____ ELEVATION _____ NORTHINGS (Y) _____ EASTINGS (X) _____

SKETCH: (Include reference tie or witness points, remarks and topo of area)

Corner Ties:

Original Bearing Tree:

1. A White Oak, 61.5" dia., bears S 31° 09' W, 44.5'.
(no nail)

Cap Inscription

T 7 S R 21 E
 S 27 | S 26
 S 34 | S 35
 LS 4689
 1984

New Bearing Objects:

2. A 6 1/4" square concrete ROW mon., up 6", with a pin in center, bears N 74° 36' 42" W, 86.79'.
3. A 6 1/4" square concrete ROW mon., up 4", with a pin in center, bears N 15° 02' 47" W, 156.30'.
4. A 1" O.D. iron pipe, up 3", tagged LS 4261, bears N 52° 15' 57" W, 153.55'.
5. A 1" O.D. iron pipe, up 1", untagged, bears, N 0° 15' 07" E, 175.53'.

V-17
 F.B. 26/44
 Mon. Bk. 3/5
 Job No. 83-20

(Continued on back)

SURVEYOR'S CERTIFICATE

THIS CORNER RECORD WAS PREPARED BY ME OR UNDER MY DIRECTION IN COMPLIANCE WITH THE SURVEYING ACT ON _____

SIGNED: Howard Arnold Cohen

L.S. No. 4689

COUNTY SURVEYOR'S CERTIFICATE

THE CORNER RECORD WAS RECEIVED 10/12/86 1986 AND EXAMINED AND FILED 11/18/86 BY James R. Benson

TITLE: _____

DOCUMENT No. _____

STATEMENT ON BACK OF SHEET YES NO

6. A 1" O.D. iron pipe, up 2", untagged, bears N 0° 27' 28" E, 176.04'.
7. A 1" O.D. iron pipe, up 7", untagged, bears N 0° 15' 56" E, 78.99'.
8. A chiseled "+" in a 25' x 15' x 10' high boulder, bears N 76° 16' 57" W, 187.48'.
9. A chiseled "+" in a 30' x 20' x 5' high boulder, bears N 23° 18' 06" E, 119.71'.
10. A power pole (SE'ly pole of twin supports), bears S 61° 48' 59" E, 5.41'.
(3 wire power lines run S 84° E and S 81° W from pole).

The centerline of Cavin Lane lies 46' west of the corner and the centerline of State Hwy. 41 lies 128' north of the corner.

Bearings are to the center of trees at the base. Distances are horizontal to a nail and tag (stamped LS 4689) driven into the side center of the root crown, unless otherwise noted.

Stamped the monument in accordance with the BLM 1973 "Manual of Surveying Instructions".

0721500200

