CORNER RECORD

COKNER	KECOKD	
	E. M.D.B. & M. MEHOIAN CA	LIFORNEA
COZNER TYPE GOVT. CORNER MEANOER RANCHO	CONTROL CONTROL CONTROL	
CORNER IDENTIFICATION — DATE OF VISIT March 61	19_84	
The court porth 1/64 corner of	i continu E 7/22	
The south-north 1/64 corner of (Common to section 5 only)	section 5 1/22.	
(common to section 5 only)		
CORNER — LEFT AS FOUND TOUND AND TAGGED TREEST	TABLISHED OBLITERATED CORNER REBUILT	
PHYSICAL DESCRIPTION OF CORNER FOUNDS EVIDENCE AND METHOD USE	ED TO IDENTIFY OR REESTABLISH	
		-
The corner position was established by subdi-	vision of section procedure.	
Found and accepted a 1 1/4" O.D. iron pipe,	30" long, tagged LS 2737, up 1",	
N 51° 58' 58" W, 0.24', from the true corner	position.	
Physical description of monuments result on perpetuated Remonumented the found iron pipe with a F.S.I	M_{\star} up A^{\dagger} . Placed the found iron nine	•
inside the F.S.M Built a 2' x 2' x 6" high	h rock mound around the monument.	=
Set a metal post with Forest Service monument	t signs attached. 4' + SE of monument.	
		•
F.S.M Aluminum monument, 2 1/2" O.D., 30"	long with a 3 1/4" O.D. aluminum cap:	;
stamped for the corner, with LS 468	9, the date and the Forest Service lo	30.
CALIFORNIA COORDINATE SYSTEM ORDER: FIRST SECOND	THIRD	
STATIONS USED: NGS (USC & GS) STATE COUNTY	—	
	EASTINGS (X)	
SKETCH: (Include reference tie or witness points, remarks and topo of	t area)	
Corner Ties: (Basis of Bearings is magnetic,	dec.=16 1/2°E) Cap Inscription	
1. A Chiseled '+' in a 2' x 1' x 6" high rock	k, S-N 1/64	
bears S 23° 32' 54" W, 11.49'.	S 5	
	LS 4689	
2. A Ponderosa Pine, 18.3" dia., bears N 10°		
55.85'.		
2 2 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7		
3. A Ponderosa Pine, 13" dia., bears S 86° 26	5' E, 25.39'.	
4. A Ponderosa Pine, 15.2" dia., bears S 08°	261 P 22 001	
4 if Tonderoba Thie, 15.2 dia, bears 5 00	50 E/ 22.09 ·	
Corner lies 3' east of the remains of a N-S fenc	ce.	
Corner lies 3' east of a creek (1' wide) runnir	ng N'ly.	
	₿ •5 - 5	
	F.B. 25/80	
	Job No. 84-01	
SIAND	(Continued on back)	
SURVEYOR'S CARTIFICATE	COUNTY SURVEYOR'S CERTIFICATE	
THIS CORNER RECORD WAS PEPARED BY ME OR UNDER AN	THE CORNER MICORD WAS RECEIVED	186
DIRECTION IN CONFORMANCE WITH THE LAND SUPPTIORS WEEK	AND EXAMINED AND PRIES () () 19 8 C.	San
ON 1922	TITLE:	
SIGNED, Howard around Colus		
LS - 868 Hay L3 4689	DOCUMENT No.	
15 4639	STATEMENT ON BACK OF SHREET	
	je na programa i programa i programa 📋 🗀 🙀 NO	

Bearings are to the center of trees at the base. Distances are horizontal to a nail a tag (stamped LS 4689) driven into the side center of the root crown.

Posted Forest Service monument and bearing tree signs on trees #3 and #4.

Blazed and scribed bearing trees #3 and #4 and stamped the monument in accordance with the BLM 1973 "Manual of Surveying Instructions".

0822200640