	ER RECORD
COUNTY OF Madera T. 7 S	CALIFORNI
CONTRACTOR GOVT. CORNER MEANDER TENCHO	
The northwest corner of sect (common to sections 4, 5,	tion 9 7/22. 8 and 9)
CORNER — LEFT AS FOUND FOUND AND TAGGED	REESTABLISHED OBLITERATED CORNER REBUILT
Found and Accepted: A 1 3/4" O.D. iron pip the corner, the date and the GLO logo. For A.W. Brown, U.S. Deputy Surveyor, 1917 and notes of W.F. Benson, U.S. Deputy Surveyor	pe, with a 2 1/2" brass cap stamped for bund 2 bearing trees per GLO field notes of 1 original bearing tree per GLO field
PHYSICAL DESCRIPTION OF MONUMENTS REBUILT OR PERPETUATED	
Left the monument as found. Set a metal post with Forest Service monum	ont gione attached Alifornia
post with foldst betvice moritim	ent signs attached, 4 from the corner.
CALIFORNIA COORDINATE SYSTEM ORDER: FIRST SECONSTATIONS USED: NGS (USC & GS) STATE COUNTY	OTHER TO STATION
ZONE ELEVATION NORTHINGS (Y)	EASTINGS (X)
ner Ties:	Cap Inscription
Original Bearing Trees:	T7S R22E S5 S4
L. Pine remains, bears S 01° 07' W, 45.7'.	(1917 BT) S 8 S 9
2. A Black Cak, 32" dia., bears N 51° 46' I (healed blaze) (1878 BT)	1917 E, 16.16'.
. A Black Oak, 32" dia., bears S 60°00'	E, 59.80' (open blaze) (1917 BT)
w Bearing Objects:	
. An Incense Cedar, 19" dia., bears N 39°	36' W, 89.78'.
bears S 29° 19' 33" W, 184.77'	'x 4' high rock,
	E-9 F.B. 25/58 Job No. 84-1 (Continued on back)
THIS CORNER RECORD WAS PRIVATED BY ME OR DIVERNORM DIRECTION IN CONFORMANCE FIRM THE WAY OF THE THE WAY	THE CORNER RECORD WAS PECTATED 1986 AND EXAMINED AND PRESS OF THE STATE OF THE STAT
45 4689 45 4689	STATEMENT ON BACK OF SHEET

OF THUS

The centerline of a 10' ± wide dirt road (running N and S) lies 48' es of the corner.

A fence (running N and S) lies 7' ± W of the monument.

Bearings are to the center of trees at the base. Distances are horizontal to a nail and tag (stamped LS 4689) driven into the side center of the root crown.

Posted Forest Service monument and bearing tree signs on corner ties #5 and #6.