COMMENT TYPES GOVT. CORNER MARKET LANCHO CONTROL OTHER	COUNTY OF MADERA	7S	IER RECORD	M.D.	MERIOIAN
West 1/4 corner Section 16 7/22 CORNER - LIFF AS FOUND TOWN AND TAGGED TRESTABLISHED COLUMN TOWN THE TABLESH RECORD. Set Iron post, 3' long, 1" dia., 24" in the ground with brass cap Field notes of A.W. Brown, U.S. Surveyor, March 1917 FOUND & : GLD iron pipe with brass cap up '9" in a small rock mound ACCEPTED PHYSICAL DISCRIPTION OF MONUMENTS REBUILT OR FEDETUALTED Left GLO monument in place. Painted the 2" pipe red. Set fiberglass post 4' from the mounument with a Forest Service "Attention" sign attached. CALIFORNIA COCCEDINATE SYSTEM ORDER. FREST COUNTY OTHER STATION USED. MOS UNCE A GS OTHER TISS TO NOETHINGS ON LEVATION. DETRINGS ON LEVATION OF MONUMENTS PROBLEM TO THE STATION USED. MOS UNCE A GS OTHER TISS. N 55° W, 64.71 Ft., to a 27" Ponderosa Pine N 9° 45' W, 43.70 Ft., to a 18" Black Oak S 24° 30' E, 44.00 Ft., to a 15.5" Black Oak S 24° 30' E, 44.00 Ft., to a 10.8" Incense Cedar N 62° E, 52.8 Ft., to the remains of original bearing tree (Pine) Bearings are to the center of trees at base; distance and horizontal to nail and tag (stamped LS 4689) driven into base of trees, unless noted otherwise. Posted Forest Service Monument and Bearing Tree signs. Blazed and scribed trees and stamped monument—in accord with Bureau of Land Management 1973 "Manual of Surveying Instructions." LAND SURVEY SURVEYOR'S CHETRICATE THIS CORNER RECORD WAS PERPARED IN ME OR UNDER MY SHEED WAS PERPARED TO ME CONNERLANCE WITH THE LAND SURVEYOR'S CHETRICATE THIS CORNER RECORD WAS PERPARED TO ME OR UNDER MY SHEET SECOND WAS PERPARED TO ME OR UNDER MY SHEET SECOND WAS PERPARED TO ME OR UNDER MY SHEET SECOND WAS PERPARED TO ME OR UNDER MY SHEET SECOND WAS PERPARED TO ME OR UNDER MY SHEET SECOND WAS PERPARED TO ME OR UNDER MY SHEET SECOND WAS PERPARED TO ME OR UNDER MY SHEET SECOND WAS PERPARED TO ME OR UNDER MY SHEET SECOND WAS PERPARED TO ME OR UNDER MY SHEET SECOND WAS PERPARED TO ME OR UNDER MY SHEET SECOND WAS PERPARED TO ME OR UNDER MY SHEET SECOND WAS PERPARED TO ME OR UNDER MY SHEET SECOND WAS PERPARED TO ME	CORNER TYPE: GOYT. CORNER 🖂	MEANDER T RANCHO	CONTROL		MERICIAN
COUNTS - LEFT AS FOUND TO FOUND AND TAGGED RESTABLISHED CRITERATED CORNER TREBUNT TO PRINTED THE CORNER FOUND, PURDICAL AND METHOD USED TO DENTIFY OF RESTABLISH RECORD: Set from post, 3' long, 1" dia., 24" in the ground with brass cap Field notes of A.W. Brown, U.S. Surveyor, March 1917 POUND 5: GLO iron pipe with brass cap up 9" in a small rock mound ACCEPTED PHYSICAL DESCRIPTION OF MONUMENTS RESULT OR PERFETUATED Left GLO monument in place. Painted the 2" pipe red. Set fiberglass post 4' from the moundment with a Forest Service "Attention" sign attached. CALMORNIA COCKDINATE STRIBM ORDER. FREST COUNTY OF THE TO THE TO THE TOWN STATEM USED. NOS USE A GS STATE COUNTY OF THE TOWN OF THE TO	CORNER IDENTIFICATION - DATE OF	F VISIT January /	19 81	. —	
PAYSICAL DESCRIPTION OF CORNER FOUND, PYDENCE AND METHOD USED TO DENTITY OR RESTABLISH RECORD: Set iron post, 3' long, 1" dis., 24" in the ground with brass cap Field notes of A.W. Brown, U.S. Surveyor, March 1917 FOUND &: GLO iron pipe with brass cap up 9" in a small rock mound ACCEPTED PAYSICAL DESCRIPTION OF MCNUMENTS RESULT OR PERFITUATED Left GLO monument in place. Painted the 2" pipe red. Set fiberglass post 4' from the mounument with a Forest Service "Attention" sign attached. CALIFORNIA COCKDINATE SYSTEM ORDER. MEST SECOND THEED STATION SIGN STATION USES MGS USE & 639 STATE COUNTY OTHER STATION STATION ZOME STATION USES MGS USE & 639 STATE COUNTY OTHER STATION STATION ZOME STATION USES MGS USE & 639 STATE COUNTY OTHER STATION STATION ZOME STATION USES MGS USE & 639 STATION STATI	West	1/4 corner Section	16 7/22		
PAYSICAL DESCRIPTION OF CORNER FOUND, PYDENCE AND METHOD USED TO DENTITY OR RESTABLISH RECORD: Set iron post, 3' long, 1" dis., 24" in the ground with brass cap Field notes of A.W. Brown, U.S. Surveyor, March 1917 FOUND &: GLO iron pipe with brass cap up 9" in a small rock mound ACCEPTED PAYSICAL DESCRIPTION OF MCNUMENTS RESULT OR PERFITUATED Left GLO monument in place. Painted the 2" pipe red. Set fiberglass post 4' from the mounument with a Forest Service "Attention" sign attached. CALIFORNIA COCKDINATE SYSTEM ORDER. MEST SECOND THEED STATION SIGN STATION USES MGS USE & 639 STATE COUNTY OTHER STATION STATION ZOME STATION USES MGS USE & 639 STATE COUNTY OTHER STATION STATION ZOME STATION USES MGS USE & 639 STATE COUNTY OTHER STATION STATION ZOME STATION USES MGS USE & 639 STATION STATI	1 0-			•	
PAYSICAL DESCRIPTION OF CORNER FOUND, PYDENCE AND METHOD USED TO DENTITY OR RESTABLISH RECORD: Set iron post, 3' long, 1" dis., 24" in the ground with brass cap Field notes of A.W. Brown, U.S. Surveyor, March 1917 FOUND &: GLO iron pipe with brass cap up 9" in a small rock mound ACCEPTED PAYSICAL DESCRIPTION OF MCNUMENTS RESULT OR PERFITUATED Left GLO monument in place. Painted the 2" pipe red. Set fiberglass post 4' from the mounument with a Forest Service "Attention" sign attached. CALIFORNIA COCKDINATE SYSTEM ORDER. MEST SECOND THEED STATION SIGN STATION USES MGS USE & 639 STATE COUNTY OTHER STATION STATION ZOME STATION USES MGS USE & 639 STATE COUNTY OTHER STATION STATION ZOME STATION USES MGS USE & 639 STATE COUNTY OTHER STATION STATION ZOME STATION USES MGS USE & 639 STATION STATI					
RECORD: Set from post, 3' long, 1" dia., 24" in the ground with brass cap Field notes of A.W. Brown, U.S. Surveyor, March 1917 FOUND &: GLO iron pipe with brass cap up 9" in a small rock mound ACCEPTED PHYSICAL DISCRIPTION OF MONUMENTS REBUILT OR PERFETUATED Left GLO monument in place. Painted the 2" pipe red. Set fiberglass post 4' from the mounument with a Forest Service "Attention" sign attached. CALIFORNIA COORDINATE SYSTEM ORDER. PREST SECOND THREE STATION STATION					REBUILT
Field notes of A.W. Brown, U.S. Surveyor, March 1917 FOUND & : GLO iron pipe with brass cap up 9" in a small rock mound ACCEPTED PHYSICAL DESCRIPTION OF MCNUMENTS RESULT OR PEPETUATED Left GLO monument in place. Painted the 2" pipe red. Set fiberglass post 4' from the mounument with a Forest Service "Attention" sign attached. CALIFORNIA COORDINATE SYSTEM ORDER. PHRST SECOND THERD STATION STA	RECORD: Set iron po	FOUND, EVIDENCE AND METHO st. 3' long, 1" dia	o used to DENTIFY of 24" in the gr	RESTABLISH ound with br	ass cap
ACCEPTED PHYSICAL DESCRIPTION OF ACNUMENTS RESULT OR PERPETUATED Left GLO monument in place. Painted the 2" pipe red. Set fiberglass post 4' from the mountment with a Forest Service "Attention" sign attached. CALIFORNIA COORDINATE SYSTEM ORDER. PIRST	Field notes	of A.W. Brown, U.S	. Surveyor, Marc	h 1917	
Left GLO monument in place. Painted the 2" pipe red. Set fiberglass post 4' from the mounument with a Forest Service "Attention" sign attached. CALIFORNIA COORDINATE STSTEM CHOICE. HEST SECONO THEO STATION SIGN ACTORN STATE STATE SECONO THEO STATION STATE STATE COUNTY THEO STATION STATION STATE STATE SECONO THEO STATION STATION STATION STATE STATE SECONO STATE STATION SECONO STATION STA		ipe with brass cap	up 9" in a small	rock mound	
Left GLO monument in place. Painted the 2" pipe red. Set fiberglass post 4' from the mounument with a Forest Service "Attention" sign attached. CALIFORNIA COORDINATE SYSTEM CROPS. MRST STATE STATION STATION USED: NGS (USC & GS) STATE COUNTY COUNTY OTHER STATION STATION STATION STATION MORTHINGS (Y) SKETCH. (Include reference He or witness points, remarks and topo of area) CORNER TIES N 55° W, 64.71 Ft., to a 27" Ponderosa Pine N 9° 45' W, 43.70 Ft., to a 18" Black Oak S 24° 30' E, 98.06 Ft., to a 15.5" Black Oak S 24° 30' E, 44.00 Ft., to a 10.8" Incense Cedar N 62° E, 52.8 Ft., to the remains of original bearing tree (Pine) Bearings are to the center of trees at base; distance and horizontal to nail and tag (stamped LS 4689) driven into base of trees, unless noted otherwise. Posted Forest Service Monument and Bearing Tree signs. Blazed and scribed trees and stamped monument in accord with Bureau of Land Management 1973 "Manual of Surveying Instructions." SURTICAL SURVEYTOR'S CENTIFICATE TIMS CONNER SECORO MASS PERMARD BY ME OR UNDER MY DIRECTION IN CONFIGURATION WITH THE LAND SURVEYORS ACT December 19 81 THE CONNET SURVEYTOR'S CENTIFICATE TIME CONNET SURVEYTOR'S CENTIFICATE TIME CONNET SURVEYTOR'S CENTIFICATE THE CONNET SURVEYTOR'S ACT AND EXAMINED AND THE LAND SURVEY SURVEY SATIONARY SATIONARY SATIONARY SATIONARY SATIONARY SATIONARY SATIONARY SAT	ACCELIED				
Left GLO monument in place. Painted the 2" pipe red. Set fiberglass post 4' from the mounument with a Forest Service "Attention" sign attached. CALIFORNIA COORDINATE SYSTEM CROPS. MRST STATE STATION STATION USED: NGS (USC & GS) STATE COUNTY COUNTY OTHER STATION STATION STATION STATION MORTHINGS (Y) SKETCH. (Include reference He or witness points, remarks and topo of area) CORNER TIES N 55° W, 64.71 Ft., to a 27" Ponderosa Pine N 9° 45' W, 43.70 Ft., to a 18" Black Oak S 24° 30' E, 98.06 Ft., to a 15.5" Black Oak S 24° 30' E, 44.00 Ft., to a 10.8" Incense Cedar N 62° E, 52.8 Ft., to the remains of original bearing tree (Pine) Bearings are to the center of trees at base; distance and horizontal to nail and tag (stamped LS 4689) driven into base of trees, unless noted otherwise. Posted Forest Service Monument and Bearing Tree signs. Blazed and scribed trees and stamped monument in accord with Bureau of Land Management 1973 "Manual of Surveying Instructions." SURTICAL SURVEYTOR'S CENTIFICATE TIMS CONNER SECORO MASS PERMARD BY ME OR UNDER MY DIRECTION IN CONFIGURATION WITH THE LAND SURVEYORS ACT December 19 81 THE CONNET SURVEYTOR'S CENTIFICATE TIME CONNET SURVEYTOR'S CENTIFICATE TIME CONNET SURVEYTOR'S CENTIFICATE THE CONNET SURVEYTOR'S ACT AND EXAMINED AND THE LAND SURVEY SURVEY SATIONARY SATIONARY SATIONARY SATIONARY SATIONARY SATIONARY SATIONARY SAT					
CALIFORNIA COORDINATE SYSTEM ORDER. FIRST SECONO THERD STATION USED: MGS (USC & GS) STATE COUNTY OTHER STATION GO. SKETCH: (Include reference He or witness points, remarks and topo of area) CORNER TIES N 55° W, 64.71 Ft., to a 27" Ponderosa Pine N 9° 45' W, 43.70 Ft., to a 18" Black Oak S 71° 30' E. 98.06 Ft., to a 15.5" Black Oak S 24° 30' E, 44.00 Ft., to a 15.5" Black Oak S 24° 30' E, 52.8 Ft., to the remains of original bearing tree (Pine) Bearings are to the center of trees at base; distance and horizontal to nail and tag (stamped LS 4689) driven into base of trees, unless noted otherwise. Posted Forest Service Monument and Bearing Tree signs. Blazed and scribed trees and stamped monument in accord with Bureau of Land Management 1973 "Manual of Surveying Instructions." LAND SAND ARNOLD OCHEN SURVEYOR'S CERTIFICATE TMS CORNER RECORD WAS PREPARED BY ME OR UNDER MY DIRECTION IN CONCERN MET ON ME CORNER RECORD WAS RECORD. IN THE LAND SURVEYORS ACT WAS RECORD WAS RECORD. IN THE LAND SURVEYORS ACT WAS RECORD WAS RECORD. IN THE CORNER RECORD WAS RECORD WAS RECORD WAS RECORD WAS RECORD. IN THE CORNER RECORD WAS RECORD WAS RECORD WAS RECORD WAS R	PHYSICAL DESCRIPTION OF MONUMER	NTS RESULLT OR PERPETUATED			
CALIFORNIA COORDINATE SYSTEM ORDER. FIRST STATION SECOND THRED STATIONS USED: NGS (USC A GS) STATE COUNTY OTHER STATION STATION CONTRIBUTIONS (N) STATION COUNTY SURVIVORS (X) STATION COUNTY SURVIVORS GENERALD SYME GOR UNDER MY DIRECTION IN CORNER STATION MORTHWINGS (Y) LAND STATION COUNTY SURVIVORS GENERALD SY ME OR UNDER MY DIRECTION IN CORNER MECORD WAS PERFECT.	Left GLO monument in	place. Painted th	e 2" pipe red.	Set fibergla	ss post 4
SKETCH: (Include reference He or witness points, remarks and topo of area) SKETCH: (Include reference He or witness points, remarks and topo of area) CORNER TIES N 55° W, 64.71 Ft., to a 27" Ponderosa Pine N 9° 45' W, 43.70 Ft., to a 18" Black Oak S 17 S 1917 S 71° 30' E. 98.06 Ft., to a 15.5" Black Oak S 24° 30' E, 44.00 Ft., to a 10.8" Incense Cedar N 62° E, 52.8 Ft., to the remains of original bearing tree (Pine) Bearings are to the center of trees at base; distance and horizontal to nail and tag (stamped LS 4689) driven into base of trees, unless noted otherwise. Posted Forest Service Monument and Bearing Tree signs. Blazed and scribed trees and stamped monument in accord with Bureau of Land Management 1973 "Manual of Surveying Instructions." LAND SURVEY S CIRTIPLATE THIS CORNER RECORD WAS PREPARED BY ME OR UNDER MY DIRECTION IN COMPOSITIONS WITH THE LAND SURVEYORS CIRTIPLEATE THIS CORNER RECORD WAS PREPARED BY ME OR UNDER MY DIRECTION IN COMPOSITIONS WITH THE LAND SURVEYORS ACT ON EASON	from the mounument w	ith a Forest Servic	e "Attention" si	gn attached.	
SKETCH: (Include reference He or witness points, remarks and topo of area) SKETCH: (Include reference He or witness points, remarks and topo of area) CORNER TIES N 55° W, 64.71 Ft., to a 27" Ponderosa Pine N 9° 45' W, 43.70 Ft., to a 18" Black Oak S 17 S 1917 S 71° 30' E. 98.06 Ft., to a 15.5" Black Oak S 24° 30' E, 44.00 Ft., to a 10.8" Incense Cedar N 62° E, 52.8 Ft., to the remains of original bearing tree (Pine) Bearings are to the center of trees at base; distance and horizontal to nail and tag (stamped LS 4689) driven into base of trees, unless noted otherwise. Posted Forest Service Monument and Bearing Tree signs. Blazed and scribed trees and stamped monument in accord with Bureau of Land Management 1973 "Manual of Surveying Instructions." LAND SURVEY S CIRTIPLATE THIS CORNER RECORD WAS PREPARED BY ME OR UNDER MY DIRECTION IN COMPOSITIONS WITH THE LAND SURVEYORS CIRTIPLEATE THIS CORNER RECORD WAS PREPARED BY ME OR UNDER MY DIRECTION IN COMPOSITIONS WITH THE LAND SURVEYORS ACT ON EASON					
SKETCH: (Include reference He or witness points, remarks and topo of area) SKETCH: (Include reference He or witness points, remarks and topo of area) CORNER TIES N 55° W, 64.71 Ft., to a 27" Ponderosa Pine N 9° 45' W, 43.70 Ft., to a 18" Black Oak S 17 S 1917 S 71° 30' E. 98.06 Ft., to a 15.5" Black Oak S 24° 30' E, 44.00 Ft., to a 10.8" Incense Cedar N 62° E, 52.8 Ft., to the remains of original bearing tree (Pine) Bearings are to the center of trees at base; distance and horizontal to nail and tag (stamped LS 4689) driven into base of trees, unless noted otherwise. Posted Forest Service Monument and Bearing Tree signs. Blazed and scribed trees and stamped monument in accord with Bureau of Land Management 1973 "Manual of Surveying Instructions." LAND SURVEY S CIRTIPLATE THIS CORNER RECORD WAS PREPARED BY ME OR UNDER MY DIRECTION IN COMPOSITIONS WITH THE LAND SURVEYORS CIRTIPLEATE THIS CORNER RECORD WAS PREPARED BY ME OR UNDER MY DIRECTION IN COMPOSITIONS WITH THE LAND SURVEYORS ACT ON EASON					
SKETCH: (Include reference He or witness points, remarks and topo of area) SKETCH: (Include reference He or witness points, remarks and topo of area) CORNER TIES N 55° W, 64.71 Ft., to a 27" Ponderosa Pine N 9° 45' W, 43.70 Ft., to a 18" Black Oak S 17 S 1917 S 71° 30' E. 98.06 Ft., to a 15.5" Black Oak S 24° 30' E, 44.00 Ft., to a 10.8" Incense Cedar N 62° E, 52.8 Ft., to the remains of original bearing tree (Pine) Bearings are to the center of trees at base; distance and horizontal to nail and tag (stamped LS 4689) driven into base of trees, unless noted otherwise. Posted Forest Service Monument and Bearing Tree signs. Blazed and scribed trees and stamped monument in accord with Bureau of Land Management 1973 "Manual of Surveying Instructions." LAND SURVEY S CIRTIPLATE THIS CORNER RECORD WAS PREPARED BY ME OR UNDER MY DIRECTION IN COMPOSITIONS WITH THE LAND SURVEYORS CIRTIPLEATE THIS CORNER RECORD WAS PREPARED BY ME OR UNDER MY DIRECTION IN COMPOSITIONS WITH THE LAND SURVEYORS ACT ON EASON					
SKETCH: (Include reference tie or witness points, remarks and topo of area) CORNER TIES N 55° W, 64.71 Ft., to a 27" Ponderosa Pine N 9° 45' W, 43.70 Ft., to a 18" Black Oak S 17 S 1917 S 71° 30' E. 98.06 Ft., to a 15.5" Black Oak S 24° 30' E, 44.00 Ft., to a 10.8" Incense Cedar N 62° E, 52.8 Ft., to the remains of original bearing tree (Pine) Bearings are to the center of trees at base; distance and horizontal to nail and tag (stamped LS 4689) driven into base of trees, unless noted otherwise. Posted Forest Service Monument and Bearing Tree signs. Blazed and scribed trees and stamped monument in accord with Bureau of Land Management 1973 "Manual of Surveying Instructions." COUNTY SURVIVOYS CIRTIFICATE THIS CORNER RECORD VAS PREPARED BY ME OR UNDER MY DIRECTION IN CONFORMANCE WITH THE LAND SURVEYORS ACT ON IS CARRED AND MED AND ME			· —		STATION
N 55° W, 64.71 Ft., to a 27" Ponderosa Pine N 9° 45' W, 43.70 Ft., to a 18" Black Oak S 17 S 1917 S 71° 30' E. 98.06 Ft., to a 15.5" Black Oak S 24° 30' E, 44.00 Ft., to a 10.8" Incense Cedar N 62° E, 52.8 Ft., to the remains of original bearing tree (Pine) Bearings are to the center of trees at base; distance and horizontal to nail and tag (stamped LS 4689) driven into base of trees, unless noted otherwise. Posted Forest Service Monument and Bearing Tree signs. Blazed and scribed trees and stamped monument in accord with Bureau of Land Management 1973 "Manual of Surveying Instructions." LAND SURVEY SCRIPPLATE THIS CORNER RECORD WAS PERFARED BY ME OR UNDER MY DIRECTION IN CONCRUMANCE WITH THE LAND SURVEYORS ACT ON IS 46500 TO 19 81			n	EASTINGS	(X)
N 55° W, 64.71 Ft., to a 27" Ponderosa Pine 1 4 N 9° 45' W, 43.70 Ft., to a 18" Black Oak S 17 S S 71° 30' E. 98.06 Ft., to a 15.5" Black Oak S 24° 30' E, 44.00 Ft., to a 10.8" Incense Cedar N 62° E, 52.8 Ft., to the remains of original bearing tree (Pine) Bearings are to the center of trees at base; distance and horizontal to nail and tag (stamped LS 4689) driven into base of trees, unless noted otherwise. Posted Forest Service Monument and Bearing Tree signs. Blazed and scribed trees and stamped monument in accord with Bureau of Land Management 1973 "Manual of Surveying Instructions." SURVEYORS CIRTIFICATE THIS CORNER RECORD WAS PREPARED BY ME OR UNDER MY DIRECTION IN CONFORMANCE WITH THE LAND SURVEYORS ACT December 19 81 COUNTY SURVEYORS CIRTIFICATE THE CORNER RECORD WAS PREPARED BY ME OR UNDER MY DIRECTION IN CONFORMANCE WITH THE LAND SURVEYORS ACT DECEMBER RECORD WAS PREPARED BY ME OR UNDER MY DIRECTION IN CONFORMANCE WITH THE LAND SURVEYORS ACT AND EXAMINED AND PIES AND EXAMINED AND	SKETCH: (Include reference tie or	witness points, remarks and t	opo of ar ea)		
N 9° 45' W, 43.70 Ft., to a 18" Black Oak S 17 S 1917 S 71° 30' E. 98.06 Ft., to a 15.5" Black Oak S 24° 30' E, 44.00 Ft., to a 10.8" Incense Cedar N 62° E, 52.8 Ft., to the remains of original bearing tree (Pine) Bearings are to the center of trees at base; distance and horizontal to nail and tag (stamped LS 4689) driven into base of trees, unless noted otherwise. Posted Forest Service Monument and Bearing Tree signs. Blazed and scribed trees and stamped monument in accord with Bureau of Land Management 1973 "Manual of Surveying Instructions." SUD LAND SURVEYOR'S CIRTIFICATE THIS CORNER RECORD WAS PREPARED BY ME OR UNDER MY DIRECTION IN COMPONIANCE WITH THE LAND SURVEYORS ACT DECEMBER RECORD WAS PREPARED BY ME OR UNDER MY AND EXAMINED AND PLET THE CORNER RECORD WAS PREPARED BY ME OR UNDER MY AND EXAMINED AND PLET THE CORNER RECORD WAS PREPARED BY ME OR UNDER MY AND EXAMINED AND PLET THE CORNER RECORD WAS PREPARED BY ME OR UNDER MY AND EXAMINED AND PLET THE CORNER RECORD WAS PREPARED BY ME OR UNDER MY AND EXAMINED AND PLET THE CORNER RECORD WAS PREPARED BY ME OR UNDER MY AND EXAMINED AND PLET THE CORNER RECORD WAS PREPARED BY ME OR UNDER MY AND EXAMINED AND PLET THE CORNER RECORD WAS PREPARED BY ME OR UNDER MY AND EXAMINED AND PLET THE CORNER RECORD WAS PREPARED BY ME OR UNDER MY AND EXAMINED AND PLET THE CORNER RECORD WAS PREPARED BY ME OR UNDER MY AND EXAMINED AND PLET THE CORNER RECORD WAS PREPARED BY ME OR UNDER MY AND EXAMINED AND PLET THE CORNER RECORD WAS PREPARED BY ME OR UNDER MY AND EXAMINED AND PLET THE CORNER RECORD WAS PREPARED BY ME OR UNDER MY AND PLET THE CORNER RECORD WAS PREPARED BY ME OR UNDER MY AND PLET THE CORNER RECORD WAS PREPARED BY ME OR UNDER MY AND PLET THE CORNER RECORD WAS PREPARED BY ME OR UNDER MY AND PLET THE CORNER RECORD WAS PREPARED BY ME OR UNDER MY AND PLET THE CORNER RECORD WAS PREPARED BY ME OR UNDER MY AND PLET THE CORNER RECORD WAS PREPARED BY ME OR UNDER MY AND PLET THE CORNER RECORD WAS PREPARED BY ME OR UNDER MY AND PLET THE CORNER RECORD WAS PREPARED BY ME	CORNER TIES			<u>-</u>	CAP INSCRIPT
S 71° 30° E. 98.06 Ft., to a 15.5" Black Oak S 24° 30° E, 44.00 Ft., to a 10.8" Incense Cedar N 62° E, 52.8 Ft., to the remains of original bearing tree (Pine) Bearings are to the center of trees at base; distance and horizontal to nail and tag (stamped LS 4689) driven into base of trees, unless noted otherwise. Posted Forest Service Monument and Bearing Tree signs. Blazed and scribed trees and stamped monument in accord with Bureau of Land Management 1973 "Manual of Surveying Instructions." SED LAND SURVEYORS CERTIFICATE THIS CORNER RECORD WAS PREPARED BY ME OR UNDER MY DIRECTION IN COMPORATION WITH THE LAND SURVEYORS ACT December 28 UNDER MY BY AND EXAMINED AND PIETS AND PIETS AND EXAMINED AND PIETS AND PI	N 55° W, 64.71 Ft.,	to a 27" Ponderosa	Pine		1
S 71° 30° E. 98.06 Ft., to a 15.5" Black Oak S 24° 30° E, 44.00 Ft., to a 10.8" Incense Cedar N 62° E, 52.8 Ft., to the remains of original bearing tree (Pine) Bearings are to the center of trees at base; distance and horizontal to nail and tag (stamped LS 4689) driven into base of trees, unless noted otherwise. Posted Forest Service Monument and Bearing Tree signs. Blazed and scribed trees and stamped monument in accord with Bureau of Land Management 1973 "Manual of Surveying Instructions." SED LAND SURVEYORS CERTIFICATE THIS CORNER RECORD WAS PREPARED BY ME OR UNDER MY DIRECTION IN COMPORATION WITH THE LAND SURVEYORS ACT December 28 UNDER MY BY AND EXAMINED AND PIETS AND PIETS AND EXAMINED AND PIETS AND PI	N 00 /51 H /2 70 Hs	to a 198 Plack C			4 c 17 c
S 24° 30' E, 44.00 Ft., to a 10.8" Incense Cedar N 62° E, 52.8 Ft., to the remains of original bearing tree (Pine) Bearings are to the center of trees at base; distance and horizontal to nail and tag (stamped LS 4689) driven into base of trees, unless noted otherwise. Posted Forest Service Monument and Bearing Tree signs. Blazed and scribed trees and stamped monument in accord with Bureau of Land Management 1973 "Manual of Surveying Instructions." SED LAND SURVEYOR'S CIRTIFICATE THIS CORNER RECORD WAS PREPARED BY ME OR UNDER MY DIRECTION IN CONFORMANCE WITH THE LAND SURVEYORS ACT December 2011 19 81 THE CORNER RECORD WAS PREPARED BY ME OR UNDER MY DIRECTION IN CONFORMANCE WITH THE LAND SURVEYORS ACT AND EXAMINED AND MEET AND EXAMIN	N 9° 45 W, 45.70 FC	., to a lo brack o	ak		the state of the s
N 62° E, 52.8 Ft., to the remains of original bearing tree (Pine) Bearings are to the center of trees at base; distance and horizontal to nail and tag (stamped LS 4689) driven into base of trees, unless noted otherwise. Posted Forest Service Monument and Bearing Tree signs. Blazed and scribed trees and stamped monument in accord with Bureau of Land Management 1973 "Manual of Surveying Instructions." SED LAND SURVEY OF CERTIFICATE THIS CORNER RECORD WAS PREPARED SY ME OR UNDER MY DIRECTION IN CONFORMANCE WITH THE LAND SURVEYORS ACT ON EACHOR 19 81	s 71° 30' E. 98.06 F	t., to a 15.5" Blac	k Oak		
N 62° E, 52.8 Ft., to the remains of original bearing tree (Pine) Bearings are to the center of trees at base; distance and horizontal to nail and tag (stamped LS 4689) driven into base of trees, unless noted otherwise. Posted Forest Service Monument and Bearing Tree signs. Blazed and scribed trees and stamped monument in accord with Bureau of Land Management 1973 "Manual of Surveying Instructions." SED LAND SURVEY OF CERTIFICATE THIS CORNER RECORD WAS PREPARED SY ME OR UNDER MY DIRECTION IN CONFORMANCE WITH THE LAND SURVEYORS ACT ON EACHOR 19 81	g 2/0 301 ፑ ሪሪ በ0 ፑ	to a 10 8" Ince	mse Cedar	y	
Bearings are to the center of trees at base; distance and horizontal to nail and tag (stamped LS 4689) driven into base of trees, unless noted otherwise. Posted Forest Service Monument and Bearing Tree signs. Blazed and scribed trees and stamped monument in accord with Bureau of Land Management 1973 "Manual of Surveying Instructions." SED LAND SURVEYOR'S CHETHICATE THIS CORNER RECORD WAS PREPARED BY ME OR UNDER MY DIRECTION IN CONFORMANCE WITH THE LAND SURVEYOR'S ACT ON December 21 19 81 THE CORNER RECORD WAS PREPARED BY ME OR UNDER MY DIRECTION IN CONFORMANCE WITH THE LAND SURVEYOR'S ACT AND EXAMINED AND PLEE BY AND EXAMINED BY AND PLEE					
Posted Forest Service Monument and Bearing Tree signs. Blazed and scribed trees and stamped monument in accord with Bureau of Land Management 1973 "Manual of Surveying Instructions." CONTENT SURVEYOR'S CIRTIFICATE COUNTY SURVEYOR'S CIRTIFICATE	N 62° E, 52.8 Ft., t	o the remains of or	iginal bearing t	ree (Pine)	The second of th
Posted Forest Service Monument and Bearing Tree signs. Blazed and scribed trees and stamped monument in accord with Bureau of Land Management 1973 "Manual of Surveying Instructions." CONTENT SURVEYOR'S CIRTIFICATE COUNTY SURVEYOR'S CIRTIFICATE	Bearings are to the	center of trees at	base; distance a	nd horizonta	l to nail
Blazed and scribed trees and stamped monument in accord with Bureau of Land Management 1973 "Manual of Surveying Instructions." HOWARD ARNOLD OCHEN SURVEYOR'S CIRTIFICATE THIS CORNER RECORD WAS PREPARED BY ME OR UNDER MY DIRECTION IN CONFORMANCE WITH THE LAND SURVEYORS ACT ON December 19 81 19 81 ST. COMMENT AND EXAMINED AND MEET AND EXAMINED AND MEET ST. COMMENT AND MEET AND EXAMINED AND MEET ST. COMMENT AND MEET ST. COM					
Blazed and scribed trees and stamped monument in accord with Bureau of Land Management 1973 "Manual of Surveying Instructions." HOWARD ARNOLD OCHEN SURVEYOR'S CIRTIFICATE THIS CORNER RECORD WAS PREPARED BY ME OR UNDER MY DIRECTION IN CONFORMANCE WITH THE LAND SURVEYORS ACT ON December 19 81 19 81 ST. COMMENT AND EXAMINED AND MEET AND EXAMINED AND MEET ST. COMMENT AND MEET AND EXAMINED AND MEET ST. COMMENT AND MEET ST. COM	Booted Forest Corvic	e Monument and Rear	ino Tree sions		
Land Management 1973 "Manual of Surveying Instructions." HOWARD ARNOLD CONNEN SURVEYOR'S CHRIFICATE THIS CORNER RECORD WAS PREPARED BY ME OR UNDER MY DIRECTION IN CONFORMAND WITH THE LAND SURVEYORS ACT ON December 19 81 19 81 SY: MANUELL MA	rosted forest bervic	e nondment and bear	ing fice orgins.		
HOWARD ARNOLD COMEN SURVIVOR'S CIRTIFICATE THIS CORNER RECORD WAS PREPARED BY ME OR UNDER MY DIRECTION IN CONFORMAND WITH THE LAND SURVEYORS ACT ON December 19 81 12 4690					ιof
HOWARD ARNOLD CONTEN SURVEYOR'S CIRTIFICATE THIS CORNER RECORD WAS PREPARED BY ME OR UNDER MY DIRECTION IN CONFORMANCE WITH THE LAND SURVEYORS ACT ON December 19 81 19 81	Land Management 19/3	"Manual of Survey1	ng Instructions.		
HOWARD ARNOLD CONTEN SURVEYOR'S CIRTIFICATE THIS CORNER RECORD WAS PREPARED BY ME OR UNDER MY DIRECTION IN CONFORMANCE WITH THE LAND SURVEYORS ACT ON December 19 81 19 81					
THIS CORNER RECORD WAS PREPARED BY ME OR UNDER MY DIRECTION IN CONFORMANCE WITH THE LAND SURVEYORS ACT ON December 19 81 19 81	SED LAND SUA				
THIS CORNER RECORD WAS PREPARED BY ME OR UNDER MY DIRECTION IN CONFORMANCE WITH THE LAND SURVEYORS ACT ON December 19 81 19 81					—
ON December 2/ 19 81 ST. AND EXAMINED AND EX	HOWARD ARNOLD CONEN				
19 16 16 16 16 16 16 16 16 16 16 16 16 16	HOWARD ARNOLD COMEN SURVEYOR'S COM		THE CORNER		1 OR'S CERTIFICATE
	HOWARD ARNOLD CONEN SURVEYORS COR THIS CORNER RECORD WAS PREPAR DIRECTION IN CONFORMANCE WITH	RED SY ME OR UNDER MY	1	ED AND PILED	1 OR'S CERTIFICATE
	HOWARD ARNOLD COMEN SURVEYORS COR THIS CORNER RECORD WAS PREPAR DIRECTION IN CONFORMANCE WITH ON December 10	RED BY ME OR UNDER MY THE LAND SURVEYORS ACT 19 81	AND EXAMINE	RECORD WAS RECENTED AND PIET BY:	R'S CIRTIFICATE
DR. CALLED LS 4689	HOWARD ARNOLD CONEN SURVEYORS CIR THIS CORNER RECORD WAS PREPAR DIRECTION IN COMPORALAND WITH ON December 2 LS 4689	THE LAND SURVEYORS ACT 19 81 THE LAND SURVEYORS ACT 19 81	AND EXAMINE	RECORD WAS RECENTED AND PIET BY:	R'S CIRTIFICATE