CORNER	RECORD	SED LAND SI
COUNTY OF Madera T. 7 S R	22 E M.D.B. & MERRY	AN CALIFORNIA
CORNER TYPE: GOV'T. CORNER MEANDER RANCHO CORNER IDENTIFICATION - DATE OF VISIT JULY 7	CONTROL OTHER TO	HOWARD ARNOLD COHEN
	154	ward arnold asked
Northwest corner Section 28 7	/22.	[   x
		LS 4689
CORNER - LEFT AS FOUND   FOUND AND TAGGED   RE	ESTABLISMED OBLITERATED CORNER _ REBUIL	OF ON 150PM
PHYSICAL DESCRIPTION OF CORNER FOUND, EVIDENCE AND METHOD USED TO IDENTIFY OR REESTABLISH		
RECORD: An iron post, 3' long, $2''$ dia., $24'$ per GLO notes of A. W. Brown, U.S-FOUND &: A 1-3/4" O.D., I.P., $36''$ long, u ACCEPTED in a rock mound $2\frac{1}{2}$ ' at the base bearing trees.	Surveyor, 1917. p 25", with a brass cap marked:	T7S   R22E
PHYSICAL DESCRIPTION OF MONUMENTS REBUILT OR PERPETUATED		
SET: Standard FSM, up 12". Rebuilt rock mound 3' at the base and 1' high around monument. Buried GLO monument horizontally with FSM. Set a fiberglass post $4' \pm NW$ of the monument with a Forest Service "Attention" sign attached. FSM - Aluminum monument, $2\frac{1}{2}$ " 0.D., 30" long with a $3\frac{1}{4}$ " 0.D. aluminum cap; stamped for the corner, with L.S. 4689, the date, and a Forest Service logo.		
CALIFORNIA COORDINATE SYSTEM ORDER FIRST SECON STATIONS USED: NGS (USC & GS) STATE COUNTY COUNTY COUNTY NORTHINGS (Y)	OTHER STATION	STATION
(ETCH: (Include reference tie or witness points, remarks and topo of grea)		
CORNER TIES:		AP INSCRIPTION
Original Bearing Trees		T7S R22E S20 S21
A black oak, 18.0" dia., bears S 8° 43' E, 26.52'. (Healed blaze)  A live oak, 17.9" dia., bears S 78° 40' W, 25.49'. (scribing visible)  A live oak, 9.6" dia., bears N 58° 40' W, 31.11'.		
Other Bearing Objects		
A chiseled "+" in a boulder (6'x8'x8' high) in a group of large boulders in the center of an intermittent creek, bears N 85° 24' 00", 39.44'.  A chiseled "+" in a boulder (7'x4'x3' high). bears \$0° 08' 30" W, 13.45'.  A chiseled "+" in a boulder (6'x4'x2' high) on top of small clump of same size boulders, bears \$ 56° 42' 00" W, 25.49'.  A chiseled "+" in a boulder (4'x3'x4' high), bears N 17° 52' 36" W, 18.63'.  The corner lies in the bed of an intermittent creek (course N 83° E) in a rocky area.  Bearings are to the center of trees at the base. Distances are horizontal to a nail & tag (stamped L.S. 4689) driven into the side-center of the root crown.  Posted Forest Service monument and bearing tree signs.  Stamped monument in accordance with the BLM 1973 "Manual of Surveying Instruction."		
SURVE YOR'S GERTIFICATE	COUNTY SURVEYOR'S CER	
SIS CORNER RECORD WAS PREPARED BY ME OR UNDER MY LIRECTION IN CONFORMANCE WITH THE LAND SURVEYOR'S ACT ON ON ONLY 19 82	THE CORNER RECORD WAS RECIEVED	Janson
SIGNED Howard Monded Column	DOCUMENT NO.	- 1 100 21 0 1 1 1 1 1 1 1 1 1 1 1 1 1 1

STATEMENT ON BACK OF SHEET