CORNER	RECORD	GED LAND SI
county of Madera T 7 S R	22 Ε M.D.B. ε	MENICIMY CALIFORNIA
	CONTROL OTHER	HOWARD ARROLD
CORNER IDENTIFICATION - DATE OF VISIT July 6		COHEN
		Lowerd arnold Och
$-2.8-$ North $\frac{1}{4}$ corner Section 28 7/	¹ 22.	
		LS 4689
	ESTABLISHED OBLITERATED CORNER	REBUIL OF CALLO
PHYSICAL DESCRIPTION OF CORNER FOUND, EVIDENCE AND METHOD		
RECORD: A post, 4" dia,, 2" in earth, 2' a	bove, per GLO notes of W	. F. Benson, U.S. Surveyo
1878,		
ACCEPTED: A 1" O.D., I.P., 22" long, Atagge	d I S 2854 perpetuatin	a the original corner
position per parcel map No. 1159		
1 original hearing tree.		
PHYSICAL DESCRIPTION OF MONUMENTS REBUILT OR PERPETUATED		
SET: Standard FSM, up 6". Rebuilt a rock	mound $1\frac{1}{4}$ at the bace an	d 1 high around the
monument. Placed old monument upside		
SE of the monument with a Forest Serv		
FSM - Aluminum monument, $2\frac{1}{2}$ 0.D., 30 long		m cap; stamped for the
corner, with L.S. 4689, the date, and	a Forest Service logo.	
CALIFORNIA COORDINATE SYSTEM ORDER FIRST SECON	D THIRD	
	OTHER STATION	STATION
ZONE ELEVATION NORTHINGS (Y)		GS (X)
CETCH (Hard of Later Line)		
(ETCH: (include reference tie or witness points, remarks, and top	oo ot area)	
CORNER TIES:		CAP INSCRIPTION
		T7S R22E
Original Bearing Trees:		S2I
	N 10 ⁰ tot 5 02 01	4
A ponderosa pine stump, 21.6" dia., bears	N 49 40' E, 23.9'.	S28 L.S. 4689
Other Bearing Objects:		1982
other bearing objects.		.302
A live oak, 12.1" dia., (3 forks) bears N 10	6 ⁰ 50' E, 31.I' (previous	sly as a
established by L.S. 2854). <u>NOTE</u> : Diameter	, bearing, and distance	
pertain to the south fork.	1 F 71 171 (D	
A ponderosa pine, 9.1" dia., bears N 89° 50 blazed chest high). NOTE: Distance is to		
side-center of tree.	a harr and cag up J h	
A black oak, 12.3" dia., (2 forks), bears S	23° 08' W, 82.27'.	
NOTE: Diameter, bearing, and distance perta		
Distance is to a nail and tag up 4' in side-center of tree.		
A draw (course N 40 W), bears S 23° 08' W,	891.	(B
An incense cedar, 23.2" dia., bears N 30° 29 by L.S. 2854.)	o w, 30.8' (no Nail).	(Previously est. 1-67
A P.K. nail and tag, up Q.03', in a flat roo	ck outcrop bears \$ 670	2 7 ' 00'' W. 56.51'
Fence lines bear S 84° W and N 4° E from	corner.	27' 00" W, 56.51' (0ver)
SURVE YOR'S CERTIFICATE		YOR'S CERTIFICATE /
MIS CORNER RECORD WAS PREPARED BY ME OR UNDER MY	THE CORNER RECORD WAS REC	2 /
STRECTION IN CONFORMANCE WITH THE LAND SURVEYOR'S ACT		
	AND EXAMINED AND PILED	
ON Odober 18 19 82	AND EXAMINED AND PLED	igiq a Busson
SIGNED Howard arnold Color	AND EXAMINED AND PLED BY: TITLE	agig li duson

- . Blazed and scribed new bearing trees and stamped monument in accordance with the BLM 1973 "Manual of Surveying Instructions."
- . Posted Forest Service monument and bearing tree signs.
- . Bearings are to the center of trees at the base. Distances are horizintal to a nail and tag (stamped L.S. 4689) driven in the side-center of the root crown, unless otherwise noted.

082234030