


CORNER RECORD

COUNTY OF Madera T. 7 S. R. 22 E. M.D.B. & M. MERIDIAN CALIFORNIA

CORNER TYPE: GOVT. CORNER MEANDER RANCHO CONTROL OTHER
 CORNER IDENTIFICATION — DATE OF VISIT January 19 1984



The north 1/16 corner of section 29 7/22.
 (Common to sections 29 and 30)

CORNER — LEFT AS FOUND FOUND AND TAGGED REESTABLISHED OBLITERATED CORNER RESULT

PHYSICAL DESCRIPTION OF CORNER FOUND, EVIDENCE AND METHOD USED TO IDENTIFY OR REESTABLISH
 The corner position was established by subdivision of section procedure.
 A 1" O.D. iron pipe, 23" long, untagged and bent westerly, was found at the corner position.

PHYSICAL DESCRIPTION OF MONUMENTS RESULT OR PERPETUATED
 Remonumented the found iron pipe with a F.S.M., flush with ground. Buried the found iron pipe alongside the monument.
 Set a metal post with Forest Service monument signs attached, 4' ± SW of the monument.
 F.S.M. — Aluminum monument, 2 1/2" O.D., 30" long, with a 3 1/4" O.D. aluminum cap, stamped for the corner, with LS 4689, the date and the Forest Service logo.

CALIFORNIA COORDINATE SYSTEM ORDER: FIRST SECOND THIRD
 STATIONS USED: NGS (USC & GS) STATE COUNTY OTHER STATION _____ STATION _____
 ZONE _____ ELEVATION _____ NORTHINGS (N) _____ EASTINGS (E) _____

SKETCH: (Include reference tie or witness points, remarks and topo of area)

Corner Ties:

1. A forked White Oak, 9.0" dia., bears S 55° 14' W, 53.27'.
2. A White Oak, 11.9" dia., bears N 38° 04' W, 51.12'.
3. A forked Live Oak, 6.7" dia. (W'ly fork), bears S 10° 51' E, 62.92'.

Cap Inscription

N 1/16
 S 30 | S 29
 LS 4689
 1984

A fence line runs north and south from corner.
 A fence corner, with (old) fence lines running north and east, lies S 29° 15' W, 35.83' from the corner.
 A fence corner, with (new) fence lines running north and east, lies S 0° 39' E, 29.10' from the corner.

S-5
 F.B. 25/32
 Mon. Ek. 2/70
 Job No. 83-20
 (Continued on back)

SURVEYOR'S CERTIFICATE

THIS CORNER RECORD WAS PREPARED BY ME OR UNDER MY DIRECTION IN CONFORMANCE WITH THE SURVEYORS ACT ON _____

SIGNED: Howard Arnold Cohen
 L.S. No. 4689

COUNTY SURVEYOR'S CERTIFICATE

THE CORNER RECORD WAS RECEIVED 10/27/86 AND EXAMINED AND FILED 11/10/86 BY: [Signature]

TITLE: _____

DOCUMENT No. _____

STATEMENT ON BACK OF SHEET YES NO

Bearings are to the center of trees at the base. Distances are horizontal to a nail and tag (stamped LS 4689) driven into the side center of the root crown.

Posted Forest Service Monument and Bearing Tree signs on tree # 3.

Blazed and scribed tree # 3 and stamped monument in accordance with the BLM 1973 "Manual of Surveying Instructions".

0822200260

