			CORNER RE				
COUNTY OF	Madera	7 S.	22 E		D.B. & M.	MEROIAN	CALIFO
	GOYT, CORNER 🔀	MEAHOEE   Janu	arv 5	CONTROL [	отняя 🗌	-	
	7						•
1200	The west	t 1/4 corner	of section 25	9 7/22.		•	• .
マンプラ	(cor	umon to secti	ons 29 and 30	O)	•		
	1					•	•
COINSS IXET	AS FOUND 🔀	POUNG AND TAGG		<del></del>	<del></del>	<del></del>	
				SHED ONLITERATI		RESULLT 🗆	
Found and 2 1/2" dia	Accepted: A brass cap	GLO iron pip stamped for per field no	e, 1" O.D., i the corner.	ip 12", le	aning south	1000	
							•
MARIE II DECEN	TROU OF LIGHT		· · · · · · · · · · · · · · · · · · ·		<del> </del>	<del></del>	
PHISICAL DESCRI	FIICH OF MONUME	ENTS REBUILT OR PERF	PETUATED	•			
Left the m	onument as f	ound.	-				
Set a meta	l post with	Forest Service	ce monument s	ians atta	ched. 4! +	SE of +bo	
monument.	-				oned, <u> </u>	DT OF CHE	-
•		·		• .		-	
	-			•			•
		_ <del></del>	<del></del>	· ·	•	· · · · · · · · · · · · · · · · · · ·	
	ORDINATE SYSTEM O		SECOND [	THIR	, <u> </u>		
	NGS (USC & GS)		כסטאזז 🗆 🖰	OTHER 🗍 3	TATION	5TATION	
ZONE	ELEVATION	но	RTHINGS (Y)	<del></del>	EASTINGS	(X)	
ner Ties:					Cap In	scription	
1917 GLO B	earing Trees	:			•	1/4	
•		<del>-</del> /-				0 + S 29	
1. A forked bears N	Manzanita 51°27'E,	snag with 3 t 36.3'. (no na	runks,	er i same z		1917	
2. A forked bears S	Black Oak 77° 30' W,	with 3 trunks 34.9'. (heal	E, E'ly fork Led blaze) (n	20" dia., o nail)			
New Bearing				·			
3. A Black	Oak, 15.8"	dia., bears N	1 40° 47' W,	17.34'.			
4. A Black (previou	Oak, 10.7" ( usly blazed)	dia., bears N	1 26° 52' E, :	20.96'.			٠.
5. A Black	Oak, 8.1" d:	ia., bears N	87° 40' E, 3	7.66'.		Bk. 2/72	
	-		•			0. 83-20	
<del></del>	O a co	LAND S		· · - · · · · · · · · · · · · · · · · ·	(Continue	ed on back	<u>l</u>
aue annue: -	SURY TO EST	THE CONTRACTOR				R'S CIRTIFICATE	n 1 -
	CONTINUE TO THE	ED ARMOUNT ST	ER MT		ECORO WAS ESCEN	1-1-0-1	4/19 <i>8</i> 7
ON	Recta 14	BOHEN 1. BA	<i>II</i> ~	AND EXAMINE	AND THE	ed IVI	11
	IP			٠.	TITUE:	711	1994XI
SIGN	o. Grevari	f Arneld la	Mu		· · · · · · · · · · · · · · · · · · ·	<del></del>	<del></del>
LS outlet N	W 45 46	89 1	1	DOCUMENT N	·	· ·	•
	Mar /	C ACOD / T	<b>//</b> .	STATEMENT ON	BACK OF SHEET	· .	
	1800	S 4689 J				725 12	NO IT

6. A P.K. nail and tag (LS 4689), in a 5' x 4' x 4' high rock, bears S 61° 50' 08" W, 20.27'.

Bearings are to the center of trees at the base. Distances are horizontal to a nail and tag (stamped LS 4689) driven into the side center of the root crown, unless otherwise noted.

Posted Forest Service monument and Bearing Tree signs on tree # 5.

Blazed and scribed tree # 5 in accordance with the BLM 1973 "Manual of Surveying Instructions".