


CORNER RECORD

COUNTY OF Madera T. 7 S. R. 22 E. M.D.B. & M. MERIDIAN CALIFORNIA

CORNER TYPE: GOVT. CORNER MEANDER RANCHO CONTROL OTHER

CORNER IDENTIFICATION — DATE OF VISIT January 3 19 84



The west 1/4 corner of section 30 7/22.
(common to sections 30 7/22 and 25 7/21)

CORNER — LEFT AS FOUND FOUND AND TAGGED REESTABLISHED OBLITERATED CORNER RESULT

PHYSICAL DESCRIPTION OF CORNER FOUND; EVIDENCE AND METHOD USED TO IDENTIFY OR REESTABLISH

Found and Accepted: A GLO iron pipe, 1" O.D., up 7", with a 2 1/2" dia. brass cap, stamped for the corner, the date and the GLO logo. Found 1 bearing tree per field notes of A.W. Brown, U.S. Deputy Surveyor, 1917.

PHYSICAL DESCRIPTION OF MONUMENTS RESULT OR PERPETUATED

Left the monument as found.
Set a metal post with Forest Service monument signs attached, 4' ± SE of the monument.

CALIFORNIA COORDINATE SYSTEM ORDER: FIRST SECOND THIRD
STATIONS USED: NGS (USC & GS) STATE COUNTY OTHER STATION _____ STATION _____
ZONE _____ ELEVATION _____ NORTHINGS (Y) _____ EASTINGS (X) _____

SKETCH: (Include reference tie or witness points, remarks and topo of area)

Corner Ties:

- 1917 Resurvey BT:
1. A Black Oak, 33.5" dia., bears S 39° 41' E, 68.48'.
(open blaze with visible scribing)

Cap Inscription

1/4
S 25 + S 30
1917

New Bearing Objects:

2. A Ponderosa Pine, 10.8" dia., bears S 85° 53' W, 15.94'.
3. A chiseled "+" on a 15' x 7' x 5' high rock, bears S 32° 29' 26" W, 136.77'.
4. A chiseled "+" on a 6' x 4' x 3' high rock, bears S 86° 18' 50" W, 73.47'.

T-1
F.B. 19/67
Mon. Bk. 2/71
Job No. 83-20
(Continued on back)

SURVEYOR'S CERTIFICATE
THIS CORNER RECORD WAS PREPARED BY OR UNDER MY DIRECTION IN COMPLIANCE WITH THE LAND SURVEYORS ACT ON Jan 14 19 84
SIGNED: Howard Arnold Cohen
L.S. No. 4689 ES 4689



COUNTY SURVEYOR'S CERTIFICATE
THE CORNER RECORD WAS RECEIVED 10/27/1988 AND EXAMINED AND FILED 11/19/1988
BY: Howard Arnold Cohen
TITLE: _____

DOCUMENT No. _____
STATEMENT ON BACK OF SHEET YES NO

A fence line runs north and south from corner.

A fence line running east and west lies 90' \pm south of the corner.

The centerline of a 7' wide dirt road (course east-west) lies 11' \pm north of the corner.

Bearings are to the center of trees at the base. Distances are horizontal to a nail and tag (stamped LS 4689) driven into the side center of the root crown.

Posted Forest Service monument and Bearing Tree signs on tree # 2.

Blazed and scribed tree # 2 in accordance with the BLM 1973 "Manual of Surveying Instructions".

08221002406

