


# CORNER RECORD

COUNTY OF Madera T. B S. R. 21 E. M.D. \_\_\_\_\_ MERIDIAN CALIFORNIA

CORNER TYPE: GOVT. CORNER  MEANDER  RANCHO  CONTROL  OTHER

CORNER IDENTIFICATION — DATE OF VISIT April 4 19 88



Section Corner for Sections 25, 26, 35, 36


CORNER — LEFT AS FOUND  FOUND AND TAGGED  REESTABLISHED OBLITERATED CORNER  RESULT

**PHYSICAL DESCRIPTION OF CORNER FOUND; EVIDENCE AND METHOD USED TO IDENTIFY OR REESTABLISH** Found the original stone mound. There is a buckeye coppice at S83°W, 32 feet; this corresponds to the calls for an original BT. Calls to a draw, South, 33 feet and East, 66 feet, correspond to the original notes. Found ties of record by L. M. Jensen; i.e. liveoak coppice S40°W, 12.79 feet and liveoak coppice N20°W, 8.71 feet.

**PHYSICAL DESCRIPTION OF MONUMENTS REBUILT OR PERPETUATED** Installed a 3/4 x 30 inch rebar in the stone mound with a 3" aluminum cap stamped for the corner and LS4126. It is on a East slope about 4 feet south of a E/W fence. Set USFS K-tag and Survey Monument signs. Blazed and scribed the Jensen BT: liveoak coppice S40°W, 12.79.

CALIFORNIA COORDINATE SYSTEM ORDER: FIRST  SECOND  THIRD   
 STATIONS USED: NGS (USC & GS)  STATE  COUNTY  OTHER  STATION \_\_\_\_\_ STATION \_\_\_\_\_  
 ZONE \_\_\_\_\_ ELEVATION \_\_\_\_\_ NORTHINGS (Y) \_\_\_\_\_ EASTINGS (X) \_\_\_\_\_

SKETCH: (include reference tie or witness points, remarks and topo of area)



THIS CORNER RECORD WAS PREPARED BY ME OR UNDER MY DIRECTION IN CONFORMANCE WITH THE LAND SURVEYORS ACT ON April 4 19 88

SIGNED \_\_\_\_\_  
 L. or R.C.E. No. \_\_\_\_\_

SEAL

**COUNTY SURVEYOR'S CERTIFICATE**

THE CORNER RECORD WAS RECEIVED 5/10 19 88 AND EXAMINED AND FILED \_\_\_\_\_

BY: Donald L. Hansen  
 TITLE: \_\_\_\_\_

DOCUMENT No. \_\_\_\_\_

STATEMENT ON BACK OF SHEET

YES  NO