T 8S R 22E		SM 7151.4) Surve	or Cor. E1/16 y No No. <u>S36/S1</u>
Maria Hababayii.	R.D. Minerats  N.F. Sierra	County Madera	THE THE STATE OF T
Merid	N.F. STEFFA DESCRIBE CORNER MONU	0,016	<u> </u>
in the second se	none		
1 9	NOTICE TO THE PROPERTY OF THE	·	
	,	·	•
N	DESCRIBE REARING TOTAL	S OR OTHER OFFICIAL ACCES	CORIEC FOLIND
2	none	S ON OTHER OFFICIAL ACCES	SOMES FOUND
			•
PHOTO IDENTIFICATION DATA	4	•	
Photo No.			
Filed At.	1.		
Object Ident.	DESCRIBE CORNER LOCAT	ON RELATIVE TO NEAR-BY F	ATURES, ALSO HOW TO REACH CORNER
Ident. By	From Madera Coun	ty Road 274 and USFS	Road 8S64 (Old Central Can
PLANE COORDINATE POSITION DATA	Road) northerly	along Road 274 for a	pproximately 0.9 miles to
StateZone	the posted line,	thence west along 1	ine for approximately 100
×	to corner.		
Y			
Estob. By			
Signature	Title Divis ムイン3.39	ion Headquarters	Date 7100-52 (3/68)
	CORNER RE	ECORD (PERPETUATION	) )
IONUMENT: DESCRIBE NEW MONUME	NT SET, OR WORK DONE TO		NT T7S R22E
Set a standard USFS alu	NT SET, OR WORK DONE TO MINUM MONUMENT	PRESERVE EXISTING MONUME	NT T7S R22E S36
Set a standard USFS alum $2\frac{1}{2}$ " 0.D. X 30" long with	NT SET, OR WORK DONE TO MINUM MONUMENT		NT T7S R22E S36 E · 1/16
Set a standard USFS alu 2½" O.D. X 30" long with	NT SET, OR WORK DONE TO minum monument $h \ a \ 3\frac{1}{2}$ " diameter	PRESERVE EXISTING MONUME	NT T7S R22E S36
Set a standard USFS alu 2½" O.D. X 30" long with	NT SET, OR WORK DONE TO MINUM MONUMENT	PRESERVE EXISTING MONUME	NT T7S R22E S36 E · 1/16 S1
$2\frac{1}{2}$ " O.D. X 30" long with	minum monument h a 3½" diameter  withessobjects etc. est t, blazed and scrib ak, blazed and scrib ak, blazed and scri	CAP MARKED:  ABLISHED, OR WORK DONE TO ed "NBT" bears N52° bed "NBT" bears S02° bed "NBT" bears S02° cap, LS 2737, bears	T7S R22E S36 E · 1/16 S1 T8S R22E LS 5339 1995 PRESERVE EXISTING EVIDENCE 55'E, 184.36'. 17'W, 47.68'.
Set a standard USFS alur 2½" O.D. X 30" long with cap.  CCCESSORIES DESCRIBE NEW BT'S An 11" diameter Live Oak An 11" diameter Black Oa A 12" diameter Golden Oa A 5/8" diameter steel ba Set a metal post with US	witness objects etc. esta, blazed and scribak, blazed and scribak, blazed and scribak, blazed and scribak, signs 54-5 and	CAP MARKED:  CAP MARKED:  ABLISHED, OR WORK DONE TO ed "NBT" bears S89°5 bed "NBT" bears S02°5 bed "NBT" bears S02°5 Cap, LS 2737, bears 54-9, N45°E, 4'.	T7S R22E
Set a standard USFS alur 2½" O.D. X 30" long with cap.  CCESSORIES DESCRIBE NEW BT'S An 11" diameter Live Oak An 11" diameter Black Oak A 12" diameter Golden Oak A 5/8" diameter steel ba Set a metal post with US	witness objects etc. esta, blazed and scribak, blazed and scribar with an Aluminum SFS signs 54-5 and	CAP MARKED:  CAP MARKED:  ABLISHED, OR WORK DONE TO ed "NBT" bears S89°5 bed "NBT" bears S02°5 bed "NBT" bears S02°5 Cap, LS 2737, bears 54-9, N45°E, 4'.	T7S R22E
Set a standard USFS alur 2½" O.D. X 30" long with cap.  CCESSORIES : DESCRIBE NEW BT'S An 11" diameter Live Oak An 11" diameter Black Oak A 12" diameter Golden Oak A 5/8" diameter steel ba Set a metal post with US  Work Done By R. Seaman  Certified Cor Record Prepared ? Ye	witness objects etc. est t, blazed and scrib ak, blazed and scrib ak, blazed and scrib ak, blazed and scrib ar with an Aluminum EFS signs 54-5 and	CAP MARKED:  ABLISHED, OR WORK DONE TO ed "NBT" bears N52° bed "NBT" bears S02° bed "NBT" bears S02° Cap, LS 2737, bears 54-9, N45°E, 4'.	T7S R22E
Set a standard USFS alur 2½" O.D. X 30" long with cap.  CCCESSORIES DESCRIBE NEW BT'S An 11" diameter Live Oak An 11" diameter Black Oa A 12" diameter Golden Oa A 5/8" diameter steel ba Set a metal post with US  Work Done By R. Seaman  Certified Cor Record Prepared ? Ye	witness objects etc. est t, blazed and scrib ak, blazed and scrib ak, blazed and scrib ak, blazed and scrib ar with an Aluminum EFS signs 54-5 and	CAP MARKED:  ABLISHED, OR WORK DONE TO ed "NBT" bears N52° bed "NBT" bears S02° bed "NBT" bears S02° Cap, LS 2737, bears 54-9, N45°E, 4'.	T7S R22E
Set a standard USFS alur 2½" O.D. X 30" long with cap.  CCESSORIES DESCRIBE NEW BT'S An 11" diameter Live Oak An 11" diameter Black Oa A 12" diameter Golden Oa A 5/8" diameter steel ba Set a metal post with US  Work Done By R. Seaman  Certified Cor Record Prepared? Ye  Bearings are to the cent LS 5339 driven into the	witness objects etc. est t, blazed and scrib ak, blazed and scrib ak, blazed and scrib ak, blazed and scrib ar with an Aluminum EFS signs 54-5 and	CAP MARKED:  ABLISHED, OR WORK DONE TO ed "NBT" bears N52° bed "NBT" bears S02° bed "NBT" bears S02° Cap, LS 2737, bears 54-9, N45°E, 4'.	T7S R22E
Set a standard USFS alur 2½" O.D. X 30" long with cap.  CCESSORIES DESCRIBE NEW BT'S An 11" diameter Live Oak An 11" diameter Black Oak A 12" diameter Golden Oak A 5/8" diameter steel baset a metal post with US  Work Done By R. Seaman  Certified Cor Record Prepared? Ye  Bearings are to the cent LS 5339 driven into the	witness objects etc. est t, blazed and scrib ak, blazed and scrib ak, blazed and scrib ak, blazed and scrib ar with an Aluminum EFS signs 54-5 and	CAP MARKED:  ABLISHED, OR WORK DONE TO ed "NBT" bears N52° bed "NBT" bears S02° bed "NBT" bears S02° Cap, LS 2737, bears 54-9, N45°E, 4'.	T7S R22E
Set a standard USFS alur 2½" O.D. X 30" long with cap.  CCESSORIES DESCRIBE NEW BT'S An 11" diameter Live Oak An 11" diameter Black Oa A 12" diameter Golden Oa A 5/8" diameter steel ba Set a metal post with US  Work Done By R. Seaman  Certified Cor Record Prepared? Ye  Bearings are to the cent LS 5339 driven into the	witness objects etc. est t, blazed and scrib ak, blazed and scrib ak, blazed and scrib ak, blazed and scrib ar with an Aluminum EFS signs 54-5 and	CAP MARKED:  ABLISHED, OR WORK DONE TO ed "NBT" bears N52° bed "NBT" bears S02° bed "NBT" bears S02° Cap, LS 2737, bears 54-9, N45°E, 4'.	T7S R22E

Index File No.