File No T8S R2	22E B.B	CORNER RECO	SM 7151.4) Survey No.	Cor. SE 1/1 No: <u>Sec. 1</u>
Merid!.D.B.& M.		Minerats	County <u>Madera</u>	
ORNER DIAGRAM		Sierra	State <u>CA</u>	44/43-49
UNIVER DIAGRAM	DESC	RIBE CORNER MON	UMENT FOUND	
1	, N	/A	•	i i
			•	
1.4	1: 1			
L				The state of the s
- 3e4 T-	_			
- -	DESCR	IBE BEARING TREE	S OR OTHER OFFICIAL ACCESSORIES FOU	NO.
		/A		NO
	┙	***		
	6			
TOTO IDENTIFICATION D	ATA	•		
hata Na	·			
led At	· · · · · · · · · · · · · · · · · · ·	1		
bject ident	DESCR	IBE CORNER LOCAT	ION PELATIVE TO MEAN AND TO THE	
ent. By	Fre	om Madera Cour	ION RELATIVE TO NEAR-BY FEATURES, AL	SU HOW TO REACH CORNER
Signate	re r	id) weeterlar	nty Road 274 and FS Road 856	4 (Uld Central Camp
ANE COORDINATE POSITI	ON DATA Tim	e thence an	along 8S64 for approximately	1800' to the poste
ote Zone		ic, thence sot	ith along posted line for 35	O' to the corner.
tob. By		,		
Agener	8			
Signature	, †i	tle Divis	ion Headquarters . Da	[†] • FS-7100-52 (3/68)
wayan	255	7.19	Lilia	FS-7100-52 (3768)
		CORNER B	FCORD (PERPETUATION)	
DESCRIBE NE	W MONINENT SET		TECORD (PERPETUATION)	
•		, OR WORK DONE TO	RECORD (PERPETUATION) PRESERVE EXISTING MONUMENT	SE
t a standard USF	S aluminum	r, or work done to monument	PRESERVE EXISTING MONUMENT	SE
t a standard USF " O.D. X 30" 1or	FS aluminum ng with a 3½	r, or work done to monument		•
t a standard USF " O.D. X 30" lor p in rock mound.	FS aluminum ng with a 3½	r, or work done to monument	PRESERVE EXISTING MONUMENT	1/16
t a standard USF " O.D. X 30" 1or	FS aluminum ng with a 3½	r, or work done to monument	PRESERVE EXISTING MONUMENT	1/16 LS 5339
t a standard USF " O.D. X 30" 1or	FS aluminum ng with a 3½	r, or work done to monument	PRESERVE EXISTING MONUMENT	1/16
t a standard USF " O.D. X 30" lor p in rock mound.	FS aluminum ng with a 3½	on work done to monument diameter	PRESERVE EXISTING MONUMENT CAP MARKED:	1/16 LS 5339 1995 EXISTING EVIDENCE
t a standard USF " O.D. X 30" lor p in rock mound.	S aluminum ing with a $3\frac{1}{2}$, OR WORK DONE TO monument " diameter ss objects etc. Es azed and scri	CAP MARKED: TABLISHED, OR WORK DONE TO PRESERVE bed "NBT" bears N33°14'W, 50	1/16 LS 5339 1995 EXISTING EVIDENCE 6.76'.
t a standard USF " O.D. X 30" lor p in rock mound. CESSORIES DESCRIBE A 7" diameter I	S aluminum ing with a 3½ NEW BI'S WITHE Live Oak, bl	, OR WORK DONE TO monument " diameter ss OBJECTS ETC. ES azed and scri	CAP MARKED: STABLISHED, OR WORK DONE TO PRESERVE bed "NBT" bears N33°14'W, 50 bed "NBT" bears N25°36'W, 40	1/16 LS 5339 1995 EXISTING EVIDENCE 6.76'. 6.27'.
t a standard USF " O.D. X 30" lor p in rock mound. CESSORIES DESCRIBE A 7" diameter I	S aluminum ing with a 3½ NEW BI'S WITHE Live Oak, bl	, OR WORK DONE TO monument " diameter ss OBJECTS ETC. ES azed and scri	CAP MARKED: STABLISHED, OR WORK DONE TO PRESERVE bed "NBT" bears N33°14'W, 50 bed "NBT" bears N25°36'W, 40	1/16 LS 5339 1995 EXISTING EVIDENCE 6.76'. 6.27'.
t a standard USF " O.D. X 30" lor p in rock mound. CESSORIES DESCRIBE A 7" diameter I A 9" diameter I A 10" diameter	TS aluminum ing with a 3½ NEW BIT WITHELIVE Oak, bl. Golden Oak,	T, OR WORK DONE TO monument " diameter ss objects etc. Es azed and scri azed and scri blazed and s	CAP MARKED: STABLISHED, OR WORK DONE TO PRESERVE bed "NBT" bears N33°14'W, 50 bed "NBT" bears N25°36'W, 40 scribed "NBT" bears N05°51'W	1/16 LS 5339 1995 EXISTING EVIDENCE 6.76'. 6.27'.
t a standard USF " O.D. X 30" lor p in rock mound. CESSORIES DESCRIBE A 7" diameter I A 9" diameter I A 10" diameter	TS aluminum ing with a 3½ NEW BIT WITHELIVE Oak, bl. Golden Oak,	T, OR WORK DONE TO monument " diameter ss objects etc. Es azed and scri azed and scri blazed and s	CAP MARKED: STABLISHED, OR WORK DONE TO PRESERVE bed "NBT" bears N33°14'W, 50 bed "NBT" bears N25°36'W, 40 scribed "NBT" bears N05°51'W	1/16 LS 5339 1995 EXISTING EVIDENCE 6.76'. 6.27'.
t a standard USF " O.D. X 30" lor p in rock mound. CESSORIES DESCRIBE A 7" diameter I A 9" diameter I A 10" diameter	TS aluminum ing with a 3½ NEW BIT WITHELIVE Oak, bl. Golden Oak,	T, OR WORK DONE TO monument " diameter ss objects etc. Es azed and scri azed and scri blazed and s	CAP MARKED: STABLISHED, OR WORK DONE TO PRESERVE bed "NBT" bears N33°14'W, 50 bed "NBT" bears N25°36'W, 40 scribed "NBT" bears N05°51'W	1/16 LS 5339 1995 EXISTING EVIDENCE 6.76'. 6.27'.
ca standard USF O.D. X 30" lor o in rock mound. CESSORIES DESCRIBE A 7" diameter I A 9" diameter I A 10" diameter	TS aluminum ing with a 3½ NEW BIT WITHELIVE Oak, bl. Golden Oak,	T, OR WORK DONE TO monument " diameter ss objects etc. Es azed and scri azed and scri blazed and s	CAP MARKED: STABLISHED, OR WORK DONE TO PRESERVE bed "NBT" bears N33°14'W, 50 bed "NBT" bears N25°36'W, 40 scribed "NBT" bears N05°51'W	1/16 LS 5339 1995 EXISTING EVIDENCE 6.76'. 6.27'.
c a standard USF O.D. X 30" lor o in rock mound. CESSORIES DESCRIBE A 7" diameter I A 9" diameter I A 10" diameter	TS aluminum ing with a 3½ NEW BIT WITHELIVE Oak, bl. Golden Oak,	T, OR WORK DONE TO monument " diameter ss objects etc. Es azed and scri azed and scri blazed and s	CAP MARKED: STABLISHED, OR WORK DONE TO PRESERVE bed "NBT" bears N33°14'W, 50 bed "NBT" bears N25°36'W, 40 scribed "NBT" bears N05°51'W	1/16 LS 5339 1995 EXISTING EVIDENCE 6.76'. 6.27'.
c a standard USF O.D. X 30" lor o in rock mound. CESSORIES DESCRIBE A 7" diameter I A 9" diameter I A 10" diameter Set a metal pos	TS aluminum ing with a 3½ with a 3½ with with Elive Oak, bluve Oak, bluve Oak, bluve Oak, bluve Oak, st with USFS	monument " diameter ssommers etc. Es azed and scri azed and scri blazed and s signs S45°W,	CAP MARKED: STABLISHED, OR WORK DONE TO PRESERVE bed "NBT" bears N33°14'W, 50 bed "NBT" bears N25°36'W, 40 scribed "NBT" bears N05°51'W	1/16 LS 5339 1995 EXISTING EVIDENCE 6.76'. 6.27'. , 44.87'.
t a standard USF O.D. X 30" lor o in rock mound. CESSORIES DESCRIBE A 7" diameter I A 9" diameter I A 10" diameter Set a metal pos	ENEW BIT WITHELIVE Oak, bluve Oak, bluve Oak, bluve Oak, bluve oak, bluve With USFS	monument " diameter ssommeter ssommeter azed and scri azed and scri blazed and s signs S45°W,	CAP MARKED: TABLISHED, OR WORK DONE TO PRESERVE bed "NBT" bears N33°14'W, 50 bed "NBT" bears N25°36'W, 40 scribed "NBT" bears N05°51'W 4'.	1/16 LS 5339 1995 EXISTING EVIDENCE 6.76'. 6.27'. , 44.87'.
t a standard USF O.D. X 30" lor o in rock mound. CESSORIES DESCRIBE A 7" diameter I A 9" diameter I A 10" diameter Set a metal pos	ENEW BIT WITHE LIVE Oak, bl. Golden Oak, st with USFS	ss objects etc. es azed and scri azed and scri blazed and s signs S45°W,	CAP MARKED: TABLISHED OR WORK DONE TO PRESERVE bed "NBT" bears N33°14'W, 50 bed "NBT" bears N25°36'W, 40 cribed "NBT" bears N05°51'W 4'.	1/16 LS 5339 1995 EXISTING EVIDENCE 6.76'. 6.27'. , 44.87'.
t a standard USF " O.D. X 30" lor p in rock mound. CESSORIES DESCRIBE A 7" diameter I A 9" diameter I A 10" diameter I Set a metal pos	ENEW BIT WITHE LIVE Oak, bl. Golden Oak, st with USFS	ss objects etc. es azed and scri azed and scri blazed and s signs S45°W,	CAP MARKED: TABLISHED OR WORK DONE TO PRESERVE bed "NBT" bears N33°14'W, 50 bed "NBT" bears N25°36'W, 40 cribed "NBT" bears N05°51'W 4'.	1/16 LS 5339 1995 EXISTING EVIDENCE 6.76'. 6.27'. , 44.87'.
t a standard USF " O.D. X 30" lor p in rock mound. CESSORIES DESCRIBE A 7" diameter I A 9" diameter I A 10" diameter I Set a metal pos	ENEW BIT WITHELIVE Oak, bl. Live Oak, bl. Golden Oak, st with USFS	monument " diameter ssommeter ssommeter azed and scri azed and scri blazed and s signs S45°W, the trees.	CAP MARKED: STABLISHED, OR WORK DONE TO PRESERVE bed "NBT" bears N33°14'W, 50 bed "NBT" bears N25°36'W, 40 bears N05°51'W 4'.	1/16 LS 5339 1995 EXISTING EVIDENCE 6.76'. 6.27'. , 44.87'.
t a standard USF O.D. X 30" lor p in rock mound. CCESSORIES DESCRIBE A 7" diameter I A 9" diameter I A 10" diameter Set a metal pose of the Core Record Preservings are to the 5339 driven in	ENEW BIT WITHELIVE Oak, bluve Oak, bluve Oak, bluve Oak, bluve With USFS with USFS	monument " diameter ssommeter ssommeter azed and scri azed and scri blazed and s signs S45°W, the trees.	CAP MARKED: TABLISHED OR WORK DONE TO PRESERVE bed "NBT" bears N33°14'W, 50 bed "NBT" bears N25°36'W, 40 cribed "NBT" bears N05°51'W 4'.	1/16 LS 5339 1995 EXISTING EVIDENCE 6.76'. 6.27'. , 44.87'.
t a standard USF " O.D. X 30" lor p in rock mound. CCESSORIES DESCRIBE A 7" diameter I A 9" diameter I A 10" diameter Set a metal pos Cork Done B, R. Sea erliked Cor Record Pre- arings are to the 5339 driven in	ENEW BIT WITHELIVE Oak, bluve Oak, bluve Oak, bluve Oak, bluve With USFS with USFS	monument " diameter ssommeter ssommeter azed and scri azed and scri blazed and s signs S45°W, the trees.	CAP MARKED: STABLISHED, OR WORK DONE TO PRESERVE bed "NBT" bears N33°14'W, 50 bed "NBT" bears N25°36'W, 40 bears N05°51'W 4'.	1/16 LS 5339 1995 EXISTING EVIDENCE 6.76'. 6.27'. , 44.87'.
t a standard USF " O.D. X 30" lor p in rock mound. CESSORIES DESCRIBE A 7" diameter I A 9" diameter I A 10" diameter I Set a metal pos	ENEW BIT WITHELIVE Oak, bluve Oak, bluve Oak, bluve Oak, bluve With USFS with USFS	monument " diameter ssommeter ssommeter azed and scri azed and scri blazed and s signs S45°W, the trees.	CAP MARKED: STABLISHED, OR WORK DONE TO PRESERVE bed "NBT" bears N33°14'W, 50 bed "NBT" bears N25°36'W, 40 bears N05°51'W 4'.	1/16 LS 5339 1995 EXISTING EVIDENCE 6.76'. 6.27'. , 44.87'.
t a standard USF " O.D. X 30" lor p in rock mound. CCESSORIES DESCRIBE A 7" diameter I A 9" diameter I A 10" diameter Set a metal pos Cork Done B, R. Sea erliked Cor Record Pre- arings are to the 5339 driven in	ENEW BIT WITHELIVE Oak, bluve Oak, bluve Oak, bluve Oak, bluve With USFS with USFS	monument " diameter ssommeter ssommeter azed and scri azed and scri blazed and s signs S45°W, the trees.	CAP MARKED: STABLISHED, OR WORK DONE TO PRESERVE bed "NBT" bears N33°14'W, 50 bed "NBT" bears N25°36'W, 40 bears N05°51'W 4'.	1/16 LS 5339 1995 EXISTING EVIDENCE 6.76'. 6.27'. , 44.87'.
t a standard USF " O.D. X 30" lor p in rock mound. CCESSORIES DESCRIBE A 7" diameter I A 9" diameter I A 10" diameter Set a metal pos Cork Done B, R. Sea erliked Cor Record Pre- arings are to the 5339 driven in	ENEW BIT WITHELIVE Oak, bluve Oak, bluve Oak, bluve Oak, bluve With USFS with USFS	monument " diameter ssommeter ssommeter azed and scri azed and scri blazed and s signs S45°W, the trees.	CAP MARKED: STABLISHED, OR WORK DONE TO PRESERVE bed "NBT" bears N33°14'W, 50 bed "NBT" bears N25°36'W, 40 bears N05°51'W 4'.	1/16 LS 5339 1995 EXISTING EVIDENCE 6.76'. 6.27'. , 44.87'.
cessories described A 7" diameter I A 10" diameter I A 10" diameter Set a metal posential Cor Record Presarings are to the 5339 driven in	ENEW BIT WITHELIVE Oak, bluve Oak, bluve Oak, bluve Oak, bluve With USFS with USFS	monument " diameter ssommeter ssommeter azed and scri azed and scri blazed and s signs S45°W, the trees.	CAP MARKED: STABLISHED, OR WORK DONE TO PRESERVE bed "NBT" bears N33°14'W, 50 bed "NBT" bears N25°36'W, 40 bears N05°51'W 4'.	1/16 LS 5339 1995 EXISTING EVIDENCE 6.76'. 6.27'. , 44.87'.