



DESCRIBE CORNER MONUMENT FOUND
 N/A

DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND
 N/A

PHOTO IDENTIFICATION DATA
 Photo No. _____
 Filed At. _____
 Object Ident. _____
 Ident. By _____
 Signature _____

DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER
 From the intersection of Madera County Roads 221 and 222; thence northerly along said Road 221 for 2300' approx., to the ~~posted~~ 1/16 Section line; thence westerly from Road 221 along said ~~posted~~ line for 750' approx., to the corner.

PLANE COORDINATE POSITION DATA
 State _____ Zone _____
 X _____
 Y _____
 Estab. By _____
 Agency _____

Signature Robert Seaman Title L.S. 5339 Division _____ Headquarters _____ Date 6/14/95 7100-52 (3/68)

CORNER RECORD (PERPETUATION)

MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT
 Set a standard USFS aluminum monument
 2 1/2" O.D. X 30" long with a 3 1/2" diameter CAP MARKED: C-N
 cap in a 4' diameter rock mound. 1/16
 LS 5339
 1995

ACCESSORIES: DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE
 1. A 1 1/4" diameter Iron Pipe marked LS 4298 bears N65°34'14"W, 16.18'.
 2. An 8" diameter Live Oak, blazed and scribed "NBT" bears S42°17'W, 22.63'.
 3. A 7" diameter Live Oak, blazed and scribed "NBT" bears S44°31'E, 82.04'.
 4. A 14" diameter Black Oak, blazed and scribed "NBT" bears S70°42'E, 73.04'.
 5. Set metal post with signs 54-6 and 54-9 N45°W, 4'.

Work Done By R. Seaman Title L.S. Date 6/5/95 State Registration No. 5339
 Certified Cor. Record Prepared? Yes No Filed At _____ Date _____

REMARKS
 Bearings are to the center of the trees, distances are horizontal to a nail and tag LS 5339 driven into the side center of the root crown. Posted USFS monument and bearing tree signs as required.