COUNTY OFMadera	THE PROPERTY OF THE PROPERTY O
CORNER TYPE GOVT, CORNER MEANDER MEANDER DECEMBER 1	CONTROL OTHER [
PARE IGENTIFICATION — DATE OF VISIT DECEMBER 1	102
The northwest corner of section	n 6 8/22.
	36 7/21, sec. 1 8/21 and sec. 6 8/22)
▼T	
CORNER — LEFT AS FOUND POUND AND TAGGED REEST.	ANICUES ANITHMEN COMME
PHYSICAL DESCRIPTION OF CORNER FOUNDS EVIDENCE AND METHOD USE	
Found and Accepted: A 2 3/4" O.D. iron pipe, cap stamped for the corner and the date, in a	up II., with a 3 3/8" dia. GLU brass
Found 4 bearing trees per field notes of A.W.	Brown, H.S. Deruty Surveyor, 1917
- outer 1 post mig choop per riche 110000 of 11111	, brown, c.p. before, parveyor, 1917.
PHYSICAL DESCRIPTION OF MONUMENTS REBUILT OR PERPETUATED	
Rebuilt rock mound 3' x 3 x 2' high around for	
Set a metal post with Forest Service monument	: signs attached, 4' ± SE
of the monument.	· .
CAUPORNIA COORDINATE SYSTEM ORDER: FIRST SECONO STATIONS USED: MGS (USC & GS) STATE COUNTY	
ZONE REVATION NORTHINGS M	OTHER STATION STATION STATION
SKETCH: (Include reference tie or witness points, remarks and topo of	area)
ner Ties:	Con Incomintion
	Cap Inscription
1917 Bearing Trees:	T 7 S
	R 21 E R 22 E
 A Black Cak, 35.5" dia., bears N 10° 39' W 	
(healed blaze)	S1 56
2. A forked Black Oak, 10" dia. (northerly fo	ork), bears 1917
N 77° 20' E, 36.00'. (healed blaze)	ork), bears
in it is a property that the property	
3. A fallen Black Oak, 24" ± dia., bears S 3°	'14' E, 39.7'.
(bearing and distance are to center of stu	mphole) (visible scribing, no nail)
4. A Black Oak, 32.6" dia., bears S 39° 36' W	1, 67.3'. (healed blaze, no nail)
New Bearing Objects:	
ten real rig. Co jects.	
5. A P.K. nail and tag (LS 4689), in a 2' x 2	2' x 18" high A-1
rock, bears N 66° 44' 10" W, 35.85'.	F.B. 19/41
	Mon. Bk. 2/78
	Job No. 83-20
<u></u> .	
TAND.	(Continued on back)
SURVEYOR CONTINUENTS SURVEYOR	(Continued on back)
THIS CORNER RECORD WAS THEFTARED BY ME OR LINES MY	(Continued on back) COUNTY SURVEYOR'S GENTIFICATE THE CORNER ESCORO WAS ENCEIVED THE CORNER
DIRECTION IN COMPOSITIONS WHO WATED ARMOUNT TOTAL	(Continued on back)
	(Continued on back) COUNTY SURVEYOR'S GENTIFICATE THE CORNER ESCORO WAS ENCEIVED THE CORNER
DIRECTION IN COMPOSITIONS WHO WATED ARMOUNT TOTAL	(Continued on back) COUNTY SURVEYOR'S STRTIFICATE THE CORNER ECORD WAS EXCELLED AND EXAMINED AND EXCELLED ST. SPECIAL STREET TITLE:
ON	(Continued on back) COUNTY SURVEYOR'S SERTIFICATE/ THE CORNER ESCORO WAS ESCRIVED ////// 1986 AND EXAMINED AND FRED /////// 1986 EY: AMAGENTAL SERVENCE ////// SERVENCE /////// SERVENCE /////// SERVENCE ///////////////////////////////////

- 6. A Black Oak, 18.8" dia., bears S 23° 09' E, 71.37'.
- 7. A Ponderosa Pine, 9.6" dia., bears S 49° 10' W, 48.06'.

Fences run N'ly, S'ly, E'ly and W'ly from a Ponderosa Pine, 23.5" dia., which lies S 31° 38' E, 10.8' from the corner.

Bearings are to the center of trees at the base. Distances are horizontal to a nail and tag (stamped LS 4689) driven into the side center of the root crown, unless otherwise noted.

Posted Forest Service monument signs on all Bearing Trees and Bearing Tree signs on trees # 6, and #7.

Blazed and scribed bearing trees #6 and #7 in accordance with the BLM 1973 " Manual of Surveying Instructions".