CORNER RECORD COUNTY OF MATCHESM CALIFORNIE CONTRATTOR GOVT. CORNER X MKHO [ MEANOER [" CONTROL [ CORNER IDENTIFICATION - DATE OF VISIT The west 1/4 corner of section 15 8/23. CORNER - LEFT AS FOUND POUND AND TAGGED [ REESTABLISHED OBLITERATED CORNER PHYSICAL DESCRIPTION OF CORNER FOUND; EVIDENCE AND METHOD USED TO IDENTIFY OR REESTABLISH Found and Accepted: A 1" O.D.I.P., 42" long, up 16", bent at base. No tag in top of pipe. This corner was reestablished by J.E. MCPheeters (LS 2854) in 1971 by single proportionate measurement. (Ref. R/S 16/146 M.C.O.R.) Found no evidence of original corner or its accessories. PHYSICAL DESCRIPTION OF MONUMENTS REBUILT OR PERPETUATED Remonumented found pipe with F.S.M., up  $4^{\rm H}$ , in a collar of stone 2' dia. around monument. Set a metal post with Forest Service monument signs attached 4' ± NW of the corner. Buried found pipe on south side of F.S.M.. F.S.M. - Aluminum monument, 2 1/2" O.D., 30" long with a 3 1/4" O.D. aluminum cap stamped for the corner, with LS 4689, the date and the Forest Service logo. \$8COND [ CALIFORNIA COORDINATE SYSTEM ORDER: FIRST | THIRD [7 STATIONS USED: NGS (USC & GS) STATE [ COUNTY [ OTHER [ STATION HORTHINGS (Y) EASTINGS (X) SKETCH: (Include reference tie or witness points, remarks and topo of area) Corner Ties: Cap Inscription T 8 S R 23 E New Bearing Objects: S 16 S 15 1. A Power Pole, bears S 81° 76' E. 34.46'. LS 4689 - 1985 2. A Chiseled "+" in a rock, 1' x 2', flush with the ground, bears S 58° 17' 43" W, 16.50'. 3. A Black Oak, 8" dia., bears N 03° 32' W, 6.69'. Bearings are to the center of tree / power pole at the base. Distances are horizontal to a nail and tag (stamped LS 4689) driven into the side center . Posted Forest Service monument and bearing tree signs. Stamped monument in accordance with the BLM 1973 " Manual of Surveying Instructions". F.B. 32/24 Job No. 85-1 THIS CORNER RECORD WAS THE CORNER RECORD WAS RECEIVED DIRECTION IN CONFORMANCE AND EXAMINED AND SHOP