CO		-	RD	

CORNER TYPE: GOVT. CORNER MEANDER 1 SANCHO CONTROL OTHER CONTROL JANUARY 29 19 85	
Northwest corner of Section 29 8/23 30 8/23.	
Common to Sections 19, 20, 29, and 30 8/23.	
CORNER — LEFT AS FOUND IN POUND AND TAGGED THE REESTABLISHED OBLITERATED CORNER	REBUILT [
Found and Accepted: A 2" O.D.I.P., up 6" with a brass cap stamp	od fam #ha 'a (.
cap inscription). in a 2' dia. rock mound, flush with the ground	. Found 3 orginal h
trees per GLO field notes of James R. Glover, U.S. Deputy Survey	or, 1878.
PHYSICAL DESCRIPTION OF MONUMENTS REBUILT OR PERPETUATED	
Left monument as found. Set a metal post with Forest Service mo	nument signs attache
3' + SW of corner.	-
CALIFORNIA COORDINATE SYSTEM ORDER: FIRST   SECOND   THIRD	
STATIONS USED: NGS (USC & GS) STATE COUNTY OTHER STATION	STATION
ZONE BLEVATION NORTHINGS (Y) B	ASTINGS (X)
SKETCH: (Include reference tie or witness points, remarks and topo of area)	Cap Inscripti
Corner Ties:	LS 2737
Original Bearing Trees:	T8S R23E
1. A White Oak, 44" dia., bears N 71° 19' W, 47.1'. (no nail)	S 19   S 20
2. A White Oak, 35" dia., bears S 32° 30' E, 48.4'. (no nail)	S 30 S 29
3. A fallen Oak, bears S 22° 33'W, 61.3'. (no nail)	3 . 17 . 196
New Bearing Objects:	W. O. GENTRY
4. A White Oak, 11" dia., bears N 61° 27' E, 35.49'.	
5. A White Oak, 16" dia., bears S 73° 52' E, 16.60'.	
6. A chiseled '+', bears S 63° 41' 13"W, 53.32'.	
7. A White Oak, 8" dia., bears N 47° 47' W, 47.26'.	
. Bearings are to the center of trees at the base. Distances are	
and tag (stamped LS 4689) driven into the side center of the root noted.	t crown, unless othe
noted.	Y7 Y1
EN LAND CO	F.B. Job No
COUNTY	SURVEYOR'S CERTIFICATE /
THIS CORNER BY ORD WINDWARD ARTHUD ME OF UNDER MY THE CORNER BECORD WA	
DIRECTION IN TONIFRMANCE METATIVE LAND STATEMENT AND EXAMINED AND FRA	munici () Sus
#*** # 7	
ware formed amed John	7