CORNER RECORD		
COUNTY OF Madera 7. 8S 8. 23E M.D.B.&	MERIDIAN	CALIFORNIA
CORNER TYPE: GOVT. CORNER MEANDER 5 RANCHO CONTROL OTHER K) CORNER HOENTIFICATION — DATE OF VISIT May 5 NE 1/16 corner of section 30 8/23. (NW corner of the SE 4 NE 1/4 of section 30 8/23.)		
CORNER — LEFT AS FOUND FOUND AND TAGGED REESTABLISHED OBLITERATED CORNER		
PHYSICAL DESCRIPTION OF CORNER POUND, EVIDENCE AND METHOD USED TO IDENTIFY OR REESTABLISH	REBUILT	
COMPANDE TO ME MENTON COSED TO IDENTIFY OR RECOINGUE		
Corner position established by subdivision of section survey.		
<u>-</u>		
PHYSICAL DESCRIPTION OF MONUMENTS REBUILT OR PERPETUATED		
Set F.S.M., up 7". Set a metal post with Forest Service monument 4'± NE of the corner.	signs attached	
	luminum cap;	
F.S.M Aluminum monument, $2\frac{1}{2}$ " O.D., 30" long with a $3\frac{1}{4}$ " O.D. a Stamped for the corner, with LS 4689, the date and the Forest Ser	vice logo.	
Stamped for the corner, with LS 4689, the date and the Forest Ser CALIFORNIA COORDINATE SYSTEM ORDER: FIRST SECOND THIRD COUNTY OTHER STATION STATIONS USED: NGS (USC & OS) STATE COUNTY OTHER STATION	vice logo. STATION	
Stamped for the corner, with LS 4689, the date and the Forest Ser CALIFORNIA COORDINATE SYSTEM ORDER: FIRST SECOND THIRD STATIONS USED: NGS (USC & GS) STATE COUNTY OTHER STATION ZONE ELEVATION NORTHINGS (Y) EAST	STATION	
Stamped for the corner, with LS 4689, the date and the Forest Ser CALIFORNIA COORDINATE SYSTEM ORDER: FIRST SECOND THIRD STATIONS USED: NGS (USC & GS) STATE COUNTY OTHER STATION ZONE NORTHINGS (Y) EAST SKETCH: (Include reference tie or witness points, remarks and topo of area)	STATION	
Stamped for the corner, with LS 4689, the date and the Forest Ser CALIFORNIA COORDINATE SYSTEM ORDER: FIRST SECOND THIRD THIRD STATIONS USED: NGS (USC & OS) STATE COUNTY OTHER STATION TONE SLEVATION NORTHINGS (Y) SKETCH: (Include reference tie or witness points, remarks and topo of great) CORNER TIES:	STATION	
Stamped for the corner, with LS 4689, the date and the Forest Ser CALIFORNIA COORDINATE SYSTEM ORDER: FIRST SECOND THIRD THIRD STATIONS USED: NGS (USC & OS) STATE COUNTY OTHER STATION TONE SLEVATION NORTHINGS (Y) SKETCH: (Include reference tie or witness points, remarks and topo of great) CORNER TIES: 1. A Black Oak, 29.3" dia., bears \$34° 27E, 187.33".	NGS (X) STATION CAP INSCRIPTO	
Stamped for the corner, with LS 4689, the date and the Forest Ser CALIFORNIA COORDINATE SYSTEM ORDER: FIRST SECOND THIRD STATIONS USED: NGS (USC & GS) NGS	CAP INSCRIPTO	
Stamped for the corner, with LS 4689, the date and the Forest Ser CALIFORNIA COORDINATE SYSTEM ORDER: FIRST SECOND THIRD THIRD STATIONS USED: NGS (USC & OS) STATE COUNTY OTHER STATION TONE SLEVATION NORTHINGS (Y) SKETCH: (Include reference tie or witness points, remarks and topo of great) CORNER TIES: 1. A Black Oak, 29.3" dia., bears \$34° 27E, 187.33".	CAP INSCRIPTO NE 1/16 S30	
Stamped for the corner, with LS 4689, the date and the Forest Ser CALIFORNIA COORDINATE SYSTEM ORDER: FIRST SECOND THIRD STATIONS USED: NGS (USC & GS) NGS	CAP INSCRIPTO NE 1/16 S30 LS 4689 1985 horizontal to	ON
Stamped for the corner, with LS 4689, the date and the Forest Ser CALIFORNIA COORDINATE SYSTEM ORDER: FIRST SECOND THIRD STATION STATIONS USED: NGS (USC & GS) STATE COUNTY OTHER STATION STATION NORTHINGS (Y) SKETCH: (Include reference tie or witness points, remarks and topo of great) CORNER TIES: 1. A Black Oak, 29.3" dia., bears \$34° 27E, 187.33'. 2. A Live Oak, 4" dia., bears \$44° 20'W, 15.23'. 3. A Black Oak, 5.1" dia. (S'ly fork), bears N85° 47' W, 72.39'. Bearings are to the center of trees at the base. Distances are	CAP INSCRIPTO NE 1/16 S30 LS 4689 1985 horizontal to	ON
Stamped for the corner, with LS 4689, the date and the Forest Ser CALIFORNIA COORDINATE SYSTEM ORDER: FIRST SECOND THIRD STATIONS USED: NGS (USC & GS) STATE COUNTY OTHER STATION STATION NORTHINGS (Y) SKETCH: (Include reference fie or witness points, remarks and topo of area) CORNER TIES: 1. A Black Oak, 29.3" dia., bears \$34° 27E, 187.33'. 2. A Live Oak, 4" dia., bears \$44° 20'W, 15.23'. 3. A Black Oak, 5.1" dia. (S'ly fork), bears N85° 47' W, 72.39'. Bearings are to the center of trees at the base. Distances are a nail and tag (stamped LS 4689) driven into the side center of the side cen	CAP INSCRIPTO NE 1/16 S30 LS 4689 1985 horizontal to	ON
Stamped for the corner, with LS 4689, the date and the Forest Ser CALIFORNIA COORDINATE SYSTEM ORDER: FIRST SECOND THIRD STATION USED: NGS (USC & OS) STATE COUNTY OTHER STATION STATION NORTHINGS (Y) SKETCH: (Include reference fie or witness points, remarks and topo of area) CORNER TIES: 1. A Black Oak, 29.3" dia., bears \$34° 27E, 187.33'. 2. A Live Oak, 4" dia., bears \$44° 20'W, 15.23'. 3. A Black Oak, 5.1" dia. (S'ly fork), bears N85° 47' W, 72.39'. Bearings are to the center of trees at the base. Distances are a nail and tag (stamped LS 4689) driven into the side center of the center of the standard of the	CAP INSCRIPTO NE 1/16 S30 LS 4689 1985 horizontal to the root crown S-4 F.B. 33/06	ON
Stamped for the corner, with LS 4689, the date and the Forest Ser CALIFORNIA COORDINATE SYSTEM ORDER: FIRST SECOND THIRD STATION USED: NGS (USC & OS) STATE COUNTY OTHER STATION STATION NORTHINGS (Y) SKETCH: (Include reference fie or witness points, remarks and topo of area) CORNER TIES: 1. A Black Oak, 29.3" dia., bears \$34° 27E, 187.33'. 2. A Live Oak, 4" dia., bears \$44° 20'W, 15.23'. 3. A Black Oak, 5.1" dia. (S'ly fork), bears N85° 47' W, 72.39'. Bearings are to the center of trees at the base. Distances are a nail and tag (stamped LS 4689) driven into the side center of the center of the standard of the	CAP INSCRIPTO NE 1/16 S30 LS 4689 1985 horizontal to the root crown S-4 F.B. 33/06	ON

STAND	
THIS CORNER RECORD FOR PREPARED BY M. ST. LOPE MY DIRECTION IN CONCERNATIONARD APPROPRIES ACT ON	THE CORNER RECORD WAS RESERVED
LS 4689	STATEMENT ON BACK OF SHEET YES NO NO